

SHURE BETA 52A

Šifra: 6223
Kategorija proizvoda: Instrumentalni Mikrofoni
Proizvođač: Shure

Cena: 25.080,00 rsd

unwanted sound. A built in dynamic locking stand adapter with an integral XLR connector simplifies installation, particularly if the microphone is to be placed inside a kick drum. The stand adapter keeps the microphone position fixed and resists slipping, even when subjected to sharp blows and strong vibrations. A hardened steel mesh grille protects the Beta 52A from the abuse and wear associated with touring.

FEATURES:

Frequency response shaped specifically for kick drums and bass instruments

Studio quality performance, even at extremely high sound pressure levels

Hardened steel mesh grille that resists wear and abuse

Neodymium magnet for high signal-to-noise ratio output

Legendary Shure quality and reliability

Built-in dynamic locking stand adapter with integral XLR connector simplifies setup, especially inside a kick drum

Supercardioid pattern for high gain before feedback and superior rejection of unwanted noise

Advanced pneumatic shock mount system that minimizes transmission of mechanical noise and vibration

Low sensitivity to varying load impedance

TypeDynamic (moving coil)
Frequency Response20 to 10,000 Hz
NOTE: The curve shows on-axis response at a distance of 2 feet from a uniform sound source. Your response may vary, depending on microphone position.
Polar PatternSupercardioid, rotationally symmetrical about microphone axis

Output Level (at 1,000 Hz)Open Circuit Voltage: -64 dBV/Pa* (0.6 mV)*1 Pa = 94 dB SPL

ImpedanceRated impedance is 150 ohms (45 ohms actual) for connection to microphone inputs rated low Z

PhasingPositive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3

Maximum SPL174 dB at 1000 Hz (calculated)
ConnectorThree-pin professional audio connector (male XLR type)
CaseSilver blue enamel-painted die cast metal with hardened, matte-finished steel grille

Adjustable, Locking Stand AdapterIntegral, dynamic locking, adjustable through 180 degrees, with standard 5/8"-27 thread
Net Weight605 grams (21.6 oz)