Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

SPL GoldMike MK2



Šifra: 10978
Kategorija prozivoda: Studijska Pretpojačala
Proizvođač: SPL

Cena: 137.880,00 rsd

Koncept hibridnog pretpojačala – kombinacija tranzistorskih i lampaških stejdževa koja koristi tehnološke i sonične prednosti oba sistema: diskretnost i nizak šum tranzistora obogaćen je muzikalnom bojom lampaškog stejdža.

Nivo(i) lampaškog pretpojačala nije više fiksiran na vrednost +6 dB kao kod GoldMike-ovog prethodnika. **MK2** donosi tri različita lampaška pretpojačanja - +6 dB ostaje standard ali su pridodati i +12 dB & +18 dB. Eksperimentišite slobodno, dok ne dođete do željenog zvuka, jer **GoldMike** pruža mogućnosti za kreativnu varijabilnost.

Separacija kanala kod **GoldMike MK2** je od suštinske važnosti za stereo sliku. Board layout je stoga simetrično preslikan oko napajanja u centru (od kanala 1 do kanala 2). Rezultat je identičan protok signala koji daje prirodno izbalansiranu stereo sliku.

Broj kanala: 2

Frekvencijski odziv: ‹10 Hz do 90 kHz (-3 dB)

Ulazne impedanse – po kanalu: Microphone, XLR: 2.8 kOhms

Line In, TRS: 10 kOhms; Instrument In, TRS: 1 MOhm

Izlazna impedansa: XLR & TRS: 50 ohms

THD + N: Input level -30 dBu, Gain 30 dBu: 0.016 %; Input level -40 dBu, Gain 40 dBu: 0.017 %

Input level -50 dBu, Gain 50 dBu: 0.022 %; Input level -60 dBu, Gain 60 dBu: 0.048 %

Noise, A-weighted, R=40 ohms; Gain 0dB: -91.2 dBu

Gain 40 dB: -86.6 dBu; Gain 50 dB: -78.7 dBu; Gain 60 dB: -69.3 dBu

Dynamic Range - Gain 30 dB: 110 dB

E.I.N. Microphone Preamplifier: 128 dBu

Ground Lift: Yes

Maximum Input Level: Microphone, XLR: +7 dBu, Microphone, XLR +PAD: +28 dBu

Line In, TRS: +23 dBu, Instrument In TRS: +7 dBu, Instrument In TRS +PAD: +14 dBu

Maximum Output Level - Balanced, XLR+ TRS +26.8 dBu, Unbalanced, XLR+ TRS +21.5 dBu

CMRR: 1 KHz, Gain 30 dB: ›75 dB, 10 KHz, Gain 30 dB: ›75 dB

Fantomsko napajanje: Yes, 48 V switchable

A/D Converter: An optional A to D converter is available

Power Compatibility: Switchable, 100 to 120 V / 60 Hz, 220 to 240 V / 50 Hz, Fuse: 315 mA

Potrošnja energije: 25 W

Dimenzije: 482 x 88 x 210 mm, Težina: 4.1 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.