**lagg**e not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

Fax: +381 11 334 PIB: 106966344

E-mail: porudzbine@player.rs

MARTHN WISMANDSPLK500A

## MARTIN WISMAN SPL 500A

Šifra: 7421

Kategorija prozivoda: Aktivne Zvučne Kutije

Proizvođač: Martin Wisman

Cena: 41.880,00 rsd

## SPL 500-A Portable Powered Speaker System Key Features:

- High Impact Molded Polypropylene Enclosure
- Big Dynamic Switch Mode Power Supply
- Built- in High Efficient Class D Amplifier
- •15" Mid-Low Frequency Transducer
- 1" Compression High Frequency Driver
- 80°X 60°Coverage Pattern
- Smooth Response With High Power Handling Capcity (long Term/Max), 124dB/l27dB
- 5 Integral Suspension Points
- Complete Mounting Solutions

The SPL-500A features a molded polypropylene enclosure that it inherently weather resistant.

Amplification, mixing, and monitoring for electronic and electro-acoustic instruments.

Martin Wisman audio used advanced program techniques to create the most successful and in fl uent-ial professional speaker system. High power, efficiency, lower distortion and great low frequency extension provide an unbelievable performance.

SPL-500A can be used for live sound reinforcement, vocals, speech and music playback in entertainment, schools, pub, coffee shop and outdoor venues. Portability is one of the important factors for choice especially.

For permanent suspension or attaching brackets, the SPL-500A also has two M8 inserts on the top and bottom, two on the side, for a total of 5.

## **Technical Specification:**

RMS power: 500W PEAK power: 1000W

Freq.Range(-1 OdB ): 45Hz-19kHz Freq .Response( -3d B): 55Hz-19kHz

Rec.Hipass Frequency: 40Hz Max Calculated SPL: 127dB Horizontal Coverage: 80° Vertical Coverage: 60° LF Transducer: 15"/65mm HF Transducer: 1 "/25mm Crossover Frequency: 2.2kHz Loop/Mix Out: XLR/M,Balanced

AC Input: 220V-240 V,AC,50/60Hz, 750 Watts

Dina / LIVIVIVO). 740 mana V 475 mana V 400 mana