

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

## SUPERLUX WO518DXLR

Šifra: 01059  
Kategorija proizvoda: Lavalier i Ostali Mikrofoni  
Proizvođač: SUPERLUX

**Cena: 3.840,00 rsd**

broadcasting and video production. The extended bass frequency range of this mic makes it the best choice for cello and double bass sound pick-up.

WO518DXLR TA3F connector for PS418D preamp (either phantom power or battery)

### Features

Boosted wire mesh grille increases the HF response  
Flat and wide frequency response, high SPL, high dynamic range, low distortion

Wind screen foam to reduce those unwanted "pop" sounds

WO518TQG is for wireless systems

### Application

TV Broadcasting  
Cello  
Eastern Strings

Speech  
Double Bass

Type: Back electret, Ø6 mm (Ø0.24")  
Polar Pattern: Omni

wo518.polar not found or type unknown

Frequency Response: 60-15,000 Hz

wo518.fr not found or type unknown

Low Frequency Filter: WO518DXLR 80Hz, 12 dB/oct/(PS418D)

Sensitivity:

WO518TQG -32 dBV/Pa (25.1 mV)

WO518XLR -44 dBV/Pa (6.3 mV)

WO518DXLR Phantom: -40 dBV/Pa (10 mV) Battery: -43 dBV/Pa (7.1 mV)

Output Impedance: 200 Ω

EA0ADXLR Phantom: 200 Ω; Battery: 600 Ω

Minimum Load Impedance: 1,000 Ω

WO518DXLR Phantom:1,000 Ω;Battery:2,000 Ω

S/N Ratio: WO518XLR 72 dB

WO518DXLR Phantom: 76 dB; Battery: 75 dB

SUPERLUX WO518DXLR

### WO518

#### Miniature Omni Condenser Lavalier Microphone

The WO518 is an omni lavalier clip-on condenser microphone with a frequency response tailored to give accurate, intelligible speech recognition. It is ideally suited for the interview programs of TV

Equivalent Output Noise: WO518XLR 22 dB  
WO518DXLR Phantom: 18 dB; Battery: 19 dB

Max. SPL: WO518XLR 132 dB SPL  
WO518DXLR Phantom: 130 dB SPL; Battery: 126 dB SPL

Dynamic Range: WO518XLR 110 dB SPL  
WO518DXLR Phantom: 112 dB; Battery: 107 dB

Power Requirements: WO518TQG 1.5~9V DC  
WO518XLR 12~52V DC, 3.5 mA  
WO518DXLR Phantom: 12~52V DC, 3.5 mA; Battery: 1.5VDC AA/UM3

Finish: Black  
Connector: WO518TQG TA4F, 1.5-meter cable  
WO518XLR TA3F, 1.5-meter cable  
WO518DXLR TA3F, 1.5-meter cable

Dimensions: Microphone:  $\varnothing 8 \times 12$  mm ( $\varnothing 0.31'' \times 0.47''$ )  
WO518XLR PS418S:  $\varnothing 21 \times 106$  mm ( $\varnothing 0.83'' \times 4.18''$ );  
WO518DXLR PS418D: H  $\times$  W  $\times$  D  $84 \times 63 \times 22.5$  mm ( $3.3'' \times 2.48'' \times 0.89''$ )

Net Weight: Microphone: 20 g (0.7 oz);  
PS418S: 118 g (4.2 oz)(Only WO518XLR);  
PS418D: 245 g (8.6 oz)(Only WO518DXLR)

Accessories Furnished: WO518TQG S12 HF boost windscreen, S13 windscreen, clip,;  
WO518XLR S12 HF boost windscreen, S13 windscreen, clip, PS418S preamp  
WO518DXLR S12 HF boost windscreen, S13 windscreen, clip, 1.5V AA; alkaline battery,  
PS418D preamp

Packaging: Colorful outer packaging