

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

# TANNOY TFX 5.1 black

Šifra: 1039  
Kategorija proizvoda: Surround Zvučnici  
Proizvođač: Tannoy

Cena: 59.880,00 rsd

TANNOY TFX 5.1 black

The  
TFX

5.1 package comprises 4xTFX satellite speakers, 1xTFX centre speakers and 1xTFX subwoofer. The TFX satellite and centre channel speakers feature the latest development in Tannoy's WideBand technology with a tweeter that extends its response to over 70kHz. With new surround sound formats delivering frequencies of up to 48kHz, the TFX system is capable of capturing the uppermost harmonic detail of every effect for an incredibly

lifelike cinematic experience. Fine details are crafted with precision and texture, and mid-band compression is eliminated to reveal an open and spacious soundstage – just how the director intended.

The TFX subwoofer builds on the success and strengths of the award winning SFX model, underpinning the new Wideband TFX satellites with fast and deep bass. Inside the substantially built cabinet is a powerful built-in amplifier and a 200mm (8.00”) long-throw driver, all controlled by sophisticated electronics within the unit. The TFX subwoofer is equally well equipped for both music and movies and offers a flexible range of connection options including RCA line level and speaker level signal inputs.

TFX 5.1 is supplied with convenient wall-mounting brackets for the four satellite loudspeakers. The centre-channel TFX speaker and, if convenient, the TFX satellites can be placed on any suitably firm surface. Dedicated loudspeaker cable is supplied in a single length to be cut to size depending on the distance between your home cinema equipment and each of the speakers.

**TFX satellites**  
The TFX satellite and centre channel speakers feature the latest development in Tannoy's WideBand technology with a tweeter that extends its response to over 70kHz. With new surround sound formats delivering frequencies of up to 48kHz, the TFX system is capable of capturing the uppermost harmonic detail of every effect for an incredibly lifelike cinematic experience. Fine details are crafted with precision and texture, and mid-band compression is eliminated to reveal an open and spacious soundstage – just how the director intended.

Each cabinet is made from an advanced polymer chosen to best damp the enclosure while revised bracing delivers tighter mid-range punch. TFX satellites have been developed to communicate speed, impact and clarity while the TFX centre has been further tuned to convey the most accurate and intelligible dialogue.

The curved rear profile of each TFX satellite speaker has been meticulously calculated and streamlined to eliminate internal standing waves to offer outstanding clarity and definition. The enhanced polymer cabinets deliver a tight, fast midrange response that allows movie soundtracks and music to soar into the room. The TFX centre channel speaker has been further fine-tuned to convey the most accurate and articulate dialogue. From a pin-drop to a shattering explosion of glass, TFX delivers effortless and immersive sound just how the director intended.

main not found or type unknown

## Specifications

### TFX 5.1 Centre & Satellites

#### PERFORMANCE

Recommended amplifier power	15 – 100 W
Sensitivity (2.83 Volts @ 1m)	85 dB
Nominal impedance	6 ohms
Frequency response (-6 dB)	140 Hz - 78 kHz
Drivers	HF: 15 mm (0.6”) titanium dome, neodymium magnet system LF: 75 mm (3”) multi-fibre paper cone
Crossover frequency (LF to HF)	2.9 kHz
Magnetic shielding	Yes
Satellite weight	0.8 kg (1.9 lbs)
Satellite dimensions (H x W x D)	130.9 x 95.9 x 100 mm (5.2 x 3.8 x 3.9”)
Centre weight	1.5 kg (3.3 lbs)
Centre dimensions (H x W x D)	95.9 x 260.3 x 100 mm (3.8 x 10.3 x 3.9”)
Finish	Gloss Black, Gloss White

<b>TFX 5.1 Subwoofer</b>	
PERFORMANCE	
Power output	100 W
Frequency response (-6 dB)	45 Hz - 140 Hz
Driver	200 mm (8”) paper cone
Inputs	140 Hz - 78 kHz
Drivers	Twin phono line level or speaker level
Power requirements	120 VA max
Fuse ratings	AC 100 - 120 V / 60 Hz - Fuse: T1.6A L / 250 V AC 220 - 240 V / 50 Hz - Fuse: T800mA L / 250 V
Additional features	ON / OFF/ AUTO power function
Weight	9.0 kg (20.0 lbs)
Dimensions H x W x D	345 x 250 x 370 mm (13.6 x 9.8 x 14.6”)
Finish	Black, White

[\*\*Tannoy TFX review\*\*](#)