Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

MARTIN T Rex - Skener

Šifra: 06297
Kategorija prozivoda: Skeneri
Proizvođač: Martin



Cena: 23.880,00 rsd

The T-Rex is a 250 W scanner featuring a quad angled mirror for aggressive mid-air effects and a combined color/gobo wheel offering multiple colors and a full array of 19 gobo patterns.

An awesome force has evolved...and it's the most dangerous threat yet to lower light forms.
King of its habitat, the T-Rex is the aggressive new companion to Martin's other famous predator, the Raptor. Together they form a deadly new partnership.
Fast and furious, the T-Rex deploys its unique quad angled mirror to create a devastating salvo of effects: light beams with razor sharp intensity slice through the air, changing color and direction to the beat of the music.
And being a cold-blooded monster, the T-Rex remains cool at all times. Its high-speed cooling fan means the T-Rex is ready for action all night long.

250 W halogen lamp
1000 hour lamp included
Combined color and gobo wheel
12 gobos
19 gobos plus open
Faceted rotating parabolic reflector
Safety approvals CE
Rigorously tested for total reliability
Music triggered
Continuous operation - no cool down time needed

Physical
Length: 490 mm (19.3 in.)
Width: 164 mm (6.5 in.)
Height: 190 mm (7.5 in.)
Weight: 7.5 kg (16.5 lbs.)

Lamp
Type: 250 W, 24 V ELC halogen
Fitted as standard: Philips ELC 10H 250 W (1000 hrs.)
Socket: GX 5.3
Approved alternative lamp(s): Osram ELC 24 V/250 W (50 hrs.), Osram ELC-7/X 24 V/250 W (700 hrs.)

Dynamic Effects
Color/gobo wheel: 19 pattern gobos (11 single color, 4 multi-color, 4 non-color) + open
Motorized mirror: Quadruple angle, continuous rotation
Motorized rotating parabolic mirror dish: Multi-facet, continuous rotation

Optics
Manual focus: 2 m (6.6 ft.) - 20 m (65.6 ft.)

Control and Programming
Control: Music trig, automatic level sensitivity adjustment

Construction
Housing: Steel and aluminum


Installation
Mounting points: Adjustable floorstand/mounting bracket
Orientation: Any

Connections
AC power input: 3-pin IEC male socket


Electrical
AC power: 110-120 V, 50/60 Hz (US model)
AC power: 230-240 V, 50/60 Hz (EU model)
Main fuse: US model 5.0 AT, EU model 2.5 AT (both slow blow)

Thermal
Cooling: Forced air
Maximum ambient temperature (Ta max.): 40° C (104° F)
Maximum surface temperature, steady state, Ta=40° C: 60° C (140° F)
Total heat dissipation (calculated, +/- 10%): 920 BTU/hr.

Downloads



Product Guide vol 10



T-Rex Screensaver

Approvals

Image not found or type unknown
EU safety: EN 60598-2-17
EU EMC: EN 55 015, EN 55 103-1, EN 61 547

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.