

CELESTION TF 1225E - Zvučnik

General specifications

CELESTION TF 1225E - Zvučnik

Nominal diameter (mm/in)	305/12
Power Rating (AES, W rms)	300
Nominal Impedance (?)	8
Voice coil diameter (mm/in)	63.5/2.5
Magnet type	Ceramic
Magnet weight (kg/oz)	1.4/50
Chassis type	Pressed steel
Sensitivity (dB)	96
Frequency range (Hz)	50-3000
Coil material	Edgewound copper
Former material	Edgewound copper
Cone material	Kevlar loaded paper
Surround material	Cloth-sealed
Suspension	Single
Xmax (mm/in)	3.3/0.13
Gap depth (mm/in)	8.0/0.31
Voice coil winding width (mm/in)	14.5/0.57

Цена: 11.880,00 rsd

Small Signal Parameters

Sd (m ² /in ²)	0.053/82.29
D (m/in)	0.26/10.24
Fs (Hz)	61
Mmt (g/oz)	53.92/1.90
Mmd (g/oz)	47.01/1.66
Qms	5.19
Qes	0.45
Qts	0.41
Re (?)	6.64
Vas (lt/ft ³)	50.8/1.80
Bl (Tm)	17.51
Cms (mm/N)	0.13
Rms (kg/s)	3.97

Mounting Information

Overall diameter (mm/in)	309/12.17
Overall depth (mm/in)	139/5.47
Cut-out diameter (mm/in)	283/11.14

Mounting slot dimensions (mm/in)	Ø 7.9/0.31
Number of mounting slots	4
Mounting slot PCD range (mm/in)	297/11.69
Unit weight (kg/lb)	4.4/9.7

Packed Dimensions and Weight

Single pack size W x D x H (mm/in)	330 x 330 x 150/13.0 x 13.0 x 5.9
Single pack weight (kg/lb)	3/6.6
Multipack (60) size W x D x H (mm/in)	1080 x 980 x 880/42.5 x 38.6 x 34.6
Multipack (60) weight (kg/lb)	190/419