1090e not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

AD & X5012100nd or type unknown

The ADJ

ADJ XS 200

Šifra: 11048

Kategorija prozivoda: Roto Glave

Proizvođač: ADJ

Cena: 27.480,00 rsd

XS 200 is a new revolution in moving lights. It features a single Axis head that has continuous 360 degree tilt rotation. The XS 200 utilizes 2 x 10-Watt LED that project sharp beams of light. Its compact size and lightweight makes it ideal for mobile entertainers, small club and bars, roller rinks, bowling centers or any mobile production.

The XS 200 creates the ultimate visual effect that by mode you can access 9 different built in shows or

involves fast moving beams and color changes. In show mode you can access 9 different built in shows or create your own color palette by color mixing the RGBW LEDs via DMX control.

The XS 200 comes with 3 different operating modes; sound active mode with sound sensitivity adjustment, show mode, or DMX control, used to create your own moving light shows or color combinations. The XS 200 can be used as a stand alone unit or in master-slave set up. The XS 200 is UC IR compatible (Sold Separately). The UC IR is used to control various functions for the XS 200.

- · Single axis Moving Head
- 360-degree continuous tilt rotation
- 2 x 10W RGBW (4-in-1) LEDs
- · Pixel control of each LED
- RGBW Color Mixing in DMX mode
- 3 Operational modes: DMX, Show Mode & Sound Active
- Stand Alone or Master-slave set up
- 2 DMX Channel modes: 16 Channels & 18 Channels
- 4-Button menu system LED Display making it easy to navigate
- 9 Built-in shows
- 5-degree Beam Angle
- 5531 LUX @2M; 1242 LUX @4M (5-degree beam)
- 3-pin XLR DMX connectors
- Lifetime of the LEDs (50,000 hr. rating)
- Power consumption: 20W total
- Power Cable Length: 1.2m (IEC)
- UC IR wireless controller & Airstream IR wireless App compatible (sold Separately)
- IEC In & Out to Daisy chain Power (Connect up to 8 Fixtures)
- Multi-voltage operation: AC 100-240V 50/60Hz (IEC input only)
- Dimensions (LxWxH): 5.75" x 4" x 11.25" / 145 x 100 x 285mm
- Weight: 4 lbs. / 2 kgs.