

## AKAI RPM500 Black

Šifra: 9702  
Kategorija proizvoda: Studijski Monitori  
Proizvođač: Akai

Cena: **17.880,00 rsd.**



### A Fortress of Sound

**detalji** not found or type unknown

Engineered for meticulous reproduction of even the most complex modern music, Akai Professional's RPM500 studio monitors easily handle layer after layer of sound, providing critical detail and the tools needed to mix with confidence. The fast Kevlar® cone provides lucid low-end agility, reproducing intricate bass patterns with ease. It's authoritative sound for the craft of music production, only from Akai Professional.

#### Pure Bi-Amplified Power

RPM500 offers pure and accurate frequency response from 50Hz to 30kHz. The 90-Watt distributed Class A/B provides the woofer and tweeter dedicated amplification—80 Watts to the woofer, 40 Watts to the tweeter—meaning you get ultra-efficient power and minimal distortion. The flared rear-firing bass port delivers low-frequency depth and definition

#### Meticulous Control

Dedicated proximity and EQ-tailoring controls give you the ability to fine-tune the speaker in diverse mixing environments. RPM500 also features HF Trim, MF Boost, and LF Cutoff controls, which allow you to find the right balance in any environment. The included monitor isolation pad dramatically decreases structure-borne resonances, and the integrated radio frequency protection preserves signal purity. RPM500 includes XLR, balanced ¼-inch TRS, and RCA inputs.

#### Solid to the Core

RPM500's cabinet is painstakingly reinforced to minimize flex, combating unwanted coloration while blocking anomalies and sound artifacts from polluting your mix. The no-compromise build quality is reflected even in components you'll never see such as the recess-mounted amp, on/off transient protection, and 14-gauge wiring to transducers. RPM500 also features a built-in output current limiter, over-temperature limiter, and subsonic filter—a full array of top-notch components that you can't see but make all the difference in the purity that you hear.

### Features

Pure and accurate frequency response from 50Hz to 30kHz

90-Watt distributed Class A/B amplification provides ultra-efficient power with minimal distortion

50-Watt (38.1

40-Watt silk-dome tweeter with 1 ¼-inch (31.7mm) voice coil

Proxim

HF Trim, MF Boost, and LF Cutoff controls allow you to mix in any environment

Includ  
struct

Integrated radio frequency protection plus magnetic shielding preserves signal purity

Reces  
gaug

On/off transient protection and external mains fuse

Outpu

subsonic filter

Flared rear-firing bass port delivers low-frequency depth and definition

XLR, 1

## Specification

Dimensions (each): 12.5" x 10.1" x 8"

Weight (each): 17.2 lbs

Power

LF Driver size: 5.25 inch (133.3mm)

HF Dr

LF Driver amp: 50-Watt

HF Dr

Input: XLR, balanced 1/4 inch (6.3mm), RCA

Enclo

Frequency range: 50 Hz to 30 kHz