

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

AKAI RPM800 Black

AKAI RPM800 Black

Šifra: 9696
Kategorija proizvoda:
Proizvođač: Akai

Cena: 31.560,00 rsd

RPM800 Bi-Amplified Studio Monitor with Proximity Control

membrana not found or type unknown

A Fortress of Sound

Engineered for meticulous reproduction of even the most complex modern music, Akai Professional's RPM800 studio monitors easily handle layer after layer of sound, providing critical detail and the tools needed to mix with confidence. The fast Kevlar® cone provides lucid low-end agility, reproducing intricate bass patterns with ease. It's authoritative sound for the craft of music production, only from Akai Professional.

Pure Bi-Amplified Power

RPM800 offers pure and accurate frequency response from 38Hz to 30kHz. The 120-Watt distributed Class A/B provides the woofer and tweeter dedicated amplification—80 Watts to the woofer, 40 Watts to the tweeter—meaning you get ultra-efficient power and minimal distortion. The flared rear-firing bass port delivers low-frequency depth and definition

Meticulous Control

Dedicated proximity and EQ-tailoring controls give you the ability to fine-tune the speaker in diverse mixing environments. RPM800 also features HF Trim, MF Boost, and LF Cutoff controls, which allow you to find the right balance in any environment. The included monitor isolation pad dramatically decreases structure-borne resonances, and the integrated radio frequency protection preserves signal purity. RPM800 includes XLR, balanced ¼-inch TRS, and RCA inputs.

Solid to the Core

RPM800's cabinet is painstakingly reinforced to minimize flex, combating unwanted coloration while blocking anomalies and sound artifacts from polluting your mix. The no-compromise build quality is reflected even in components you'll never see such as the recess-mounted amp, on/off transient protection, and 14-gauge wiring to transducers. RPM800 also features a built-in output current limiter, over-temperature limiter, and subsonic filter—a full array of top-notch components that make all the difference in the purity that you hear.

ulazi not found or type unknown

Features

Pure and accurate frequency response from 38Hz to 30kHz

120-Watt distributed Class A/B amplification provides ultra-efficient power with minimal distortion
40-Watt silk-dome tweeter with 1 ¼-inch (31.7mm) voice coil
HF Trim, MF Boost, and LF Cutoff controls allow you to mix in any environment

80-W
(38.1
Proxim
Includ

structure-borne resonances	Integrated radio frequency protection plus magnetic shielding preserves signal purity	Receives
	On/off transient protection and external mains fuse	gauges
	Flared rear-firing bass port delivers low-frequency depth and definition	Output
		subsonic
		XLR, balanced

Specification

Dimensions (each): 17.1" x 14.2" x 11.3"	Weight (each): 30.1 lbs	Power
	LF Driver size: 8 inch (203.2mm)	HF D
	LF Driver amp: 80-Watt	HF D
	Input: XLR, balanced 1/4 inch (6.3mm), RCA	Enclo
	Frequency range: 38 Hz to 30 khz	