

Biamp - Apart CHAMP-3D - Razglasno pojačalo

Šifra: 12817

Kategorija proizvoda: Razglasna Pojačala

Proizvođač: Biamp - Apart

Cena: **181.080,00** rsd

The CHAMP-3D is a 3-channel fully programmable digital amplifier with all the essential features to meet your customer's expectations. This versatile power center is ideal for medium to mid-sized applications up to 2100 watts and because of its convection cooling the amplifier has no fan inside so will stay dust-free. The Hypex class-D amplifier modules inside a high damping factor is guaranteed which results in a real dynamic, warm and high-end sound. Without compromising on the advantages like low power consumption, high efficiency, low weight and a fanless design, Hypex has tackled all known disadvantages of digital amplification.

The built-in loudspeaker wizard of CHAMP-3D makes your life easy during set-up. This wizard offers you an easy way to select all Apart top cabinets and subwoofers which will now automatically be configured with the ideal DSP settings to protect your sound system and to guarantee a warm and dynamic high-end sound! With the built-in high class DSP processor you have the possibility to adjust the 4-band full parametric EQ and crossover, delay, compressor and limiter-leveler. Once all your settings have been done, you can make multiple user permission levels to avoid tampering by unauthorized or unqualified people: another guarantee for a reliable and ideal sounding sound system.

dynamic output power 4 ohms 2 x 370 watts RMS output power 4 ohms 2 x 350 watts

dynamic output power 8 ohms 2 x 250 watts RMS output power 8 ohms 2 x 225 watts

dynamic output power 2.7 ohms 2 x 530 watts subwoofer output power RMS 2 ohms 1 x 1100 watts

subwoofer dynamic output power 2 ohms 1 x 1350 watts subwoofer minimum impedance load 2 ohms

minimum impedance load per channel 2.7 ohms power consumption (max) 1500 watts

19" (483 mm wide) rack mounting yes height- rack units (1U=44 mm) 2 U

depth (build in) 345 mm depth (incl front) 378 mm

power supply 230 VAC output channels 3

line input balanced 2 tone control yes

RS232 (serial communication port) yes frequency response (in Hz) 10 - 24 k

cooling system convection applicable low impedance yes

Net weight product (kg) 16.10