

Biamp CM 20T - Plafonski zvučnik

Šifra: 5730

Kategorija proizvoda: Plafonski Zvučnici

Proizvođač: Biamp

Cena: 7.200,00 rsd

CM20T humidity proof and ideal to be used in bathrooms, kitchens... The loudspeaker is easy to install, due to its simple, quick mounting system with only 3 screws. These screws are hidden behind the loudspeaker grill, what gives the loudspeaker a modern and striking design.

This loudspeaker is now updated with a new Quick Fix connector and transformer tapping sticker for an even faster and easier installation.

Versatile for almost every market around the globe due to the addition of the 70 / 100 volt connection, the CM series is bound to stay the standard installer's choice in the fixed install market.

The complete redesign of the CM Series is done according to the corporate Apart identity. Apart blue speaker clamps and product sticker, an Apart marked transformer and loudspeaker basket.

The CM20T loudspeakers can be painted in any colour.

Biamp CM 20T - Plafonski zvučnik

The

loudspeaker has a 6.5" enforced polypropylene woofer what results in a very low distortion. To complete the sound, a 1" tweeter has been integrated. It makes the CM20T very suitable for the distribution of microphone calls and background music.

The housing is made of high quality ABS. The woofer is made out of enforced polypropylene, what makes it moisture-proof. The aluminium grille makes

Main Features

Two-way built-in loudspeaker; 16 ohms or 100 volt loudspeaker

20 watts 100 volt transformer (20 - 10 - 5 - 2.5 watts)

Versatile 70/100v connectors

Connect up to 4 speakers parallel on a standard 4 ohms amplifier

ABS housing; enforced polypropylene woofer; aluminium grille

Use for high ceilings and areas requiring reasonable power

General

Loudspeaker system: 2-way

Woofer cone material: polypropylene

Mounting system: 3 screws

70V transformer power taps: 20 - 10 - 5 - 2.5 watts

Low impedance dynamic power: 60 watts

Max SPL 1m: 104 dB

Main construction material: ABS plastic

IP rating: 54

Applicable in 100V: yes

Woofer size: 6.5inch

Tweeter size: 1 inch

100V transformer power taps: 20 - 10 - 5 watts

Impedance: 16 ohms

SPL 1W/1m: 86 dB

Frequency response: 60 - 20K Hz

Grille main material: aluminium

Applicable low impedance: yes

Vertical dispersion angle 1000 Hz: 180°

Physical & Dimensions

Outside diameter: 205mm

Cutout: 186mm

Depth: 80mm

Weight: 1.4kg