

## Biamp CM 20T - Plafonski zvučnik

Šifra: 05730

Kategorija proizvoda: Plafonski Zvučnici

Proizvođač: Biamp



**Cena: 7.200,00 rsd**

The loudspeaker has a 6.5" enforced polypropylene woofer what results in a very low distortion. To complete the sound, a 1" tweeter has been integrated. It makes the CM20T very suitable for the distribution of microphone calls and background music.

The housing is made of high quality ABS. The woofer is made out of enforced polypropylene, what makes it moisture-proof. The aluminium grille makes CM20T humidity proof and ideal to be used in bathrooms, kitchens... The loudspeaker is easy to install, due to its simple, quick mounting system with only 3 screws. These screws are hidden behind the loudspeaker grill, what gives the loudspeaker a modern and striking design.

This loudspeaker is now updated with a new Quick Fix connector and transformer tapping sticker for an even faster and easier installation.

Versatile for almost every market around the globe due to the addition of the 70 / 100 volt connection, the CM series is bound to stay the standard installer's choice in the fixed install market.

The complete redesign of the CM Series is done according to the corporate Apart identity. Apart blue speaker clamps and product sticker, an Apart marked transformer and loudspeaker basket.

The CM20T loudspeakers can be painted in any colour.

### Main Features

Two-way built-in loudspeaker; 16 ohms or 100 volt loudspeaker  
Connect up to 4 speakers parallel on a standard 4 ohms amplifier  
20 watts 100 volt transformer (20 - 10 - 5 - 2.5 watts)  
ABS housing; enforced polypropylene woofer; aluminium grille  
Versatile 70/100v connectors  
Use for high ceilings and areas requiring reasonable power

### General

Loudspeaker system: 2-way  
Woofer size: 6.5inch  
Woofer cone material: polypropylene  
Tweeter size: 1 inch  
Mounting system: 3 screws  
100V transformer power taps: 20 - 10 - 5 watts  
70V transformer power taps: 20 - 10 - 5 - 2.5 watts  
Impedance: 16 ohms  
Low impedance dynamic power: 60 watts  
SPL 1W/1m: 86 dB  
Max SPL 1m: 104 dB  
Frequency response: 60 - 20K Hz  
Main construction material: ABS plastic  
Grille main material: aluminium

IP rating: 54

Applicable low impedance: yes

Applicable in 100V: yes

Vertical dispersion angle 1000 Hz: 180°

**Physical & Dimensions**

Outside diameter: 205mm

Depth: 80mm

Cutout: 186mm

Weight: 1.4kg