Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Biamp CM 20T - Plafonski zvučnik



Šifra: 05730
Kategorija prozivoda: Plafonski Zvučnici
Proizvođač: Biamp

Cena: 7.200,00 rsd

The loudspeaker has a 6.5” enforced polypropylene woofer what results in a very low distortion. To complete the sound, a 1” tweeter has been integrated. It makes the CM20T very suitable for the distribution of microphone calls and background music.
The housing is made of high quality ABS. The woofer is made out of enforced polypropylene, what makes it moisture-proof. The aluminium grille makes CM20T humidity proof and ideal to be used in bathrooms, kitchens... The loudspeaker is easy to install, due to its simple, quick mounting system with only 3 screws. These screws are hidden behind the loudspeaker grill, what gives the loudspeaker a modern and striking design.
This loudspeaker is now updated with a new Quick Fix connector and transformer tapping sticker for an even faster and easier installation.
Versatile for almost every market around the globe due to the addition of the 70 / 100 volt connection, the CM series is bound to stay the standard installer’s choice in the fixed install market.
The complete redesign of the CM Series is done according to the corporate Apart identity. Apart blue speaker clamps and product sticker, an Apart marked transformer and loudspeaker basket.
The CM20T loudspeakers can be painted in any colour.

Main Features
Two-way built-in loudspeaker; 16 ohms or 100 volt loudspeaker
Connect up to 4 speakers parallel on a standard 4 ohms amplifier
20 watts 100 volt transformer (20 - 10 - 5 - 2.5 watts)
ABS housing; enforced polypropylene woofer; aluminium grille
Versatile 70/100v connectors
Use for high ceilings and areas requiring reasonable power

General
Loudspeaker system: 2-way
Woofer size: 6.5inch
Woofer cone material: polypropylene
Tweeter size: 1 inch
Mounting system: 3 screws
100V transformer power taps: 20 - 10 - 5 watts
70V transformer power taps: 20 - 10 - 5 - 2.5 watts
Impedance: 16 ohms
Low impedance dynamic power: 60 watts
SPL 1W/1m: 86 dB
Max SPL 1m: 104 dB
Frequency response: 60 - 20K Hz
Main construction material: ABS plastic
Grille main material: aluminium

IP rating: 54
Applicable low impedance: yes
Applicable in 100V: yes
Vertical dispersion angle 1000 Hz: 180°

Physical & Dimensions

Outside diameter: 205mm
Depth: 80mm
Cutout: 186mm
Weight: 1.4kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.