

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Biamp CMAR5 W - Plafonski zvučnik

Šifra: 6935

Kategorija proizvoda: Plafonski Zvučnici

Proizvođač: Biamp

Cena: 7.320,00 rsd

Biamp CMAR5 W - Plafonski zvučnik

logo not found or type unknown

White 5 “ build-in speaker for use in marine or very humid environments

Image not found or type unknown

[Click to enlarge picture](#)

Shape: round
Rated RMS power: 25W
Music power: 50W
Impedance: 8 Ohm
Frequency response: 100Hz to 20 KHz
SPL 1W/1m in dB: 85dB
Dispersion (at 1kHz, 2kHz, 4kHz, 8kHz in degrees): 180°,120°,120°
HP filter build in: Yes, HP on tweeter
Woofer size: 5 1/4 inch
Tweeter size: 1 inch
Color: white
Chassis Type: plastic
Grill material: stainless Steel
IP classification: IP65
Max operating temp: 95°C
Removable grill: yes
Fixing type: screws
Cut Out dimensions: 110mm
Outside dimensions: 152mm
Mounting depth: 55mm
Net Weight: 0.6kg
Gross Weight: 0.8Kg

The APart CMAR5-W marine loudspeaker has been designed especially to offer quality sound even in the most difficult, humid and hot conditions. That’s why we have combined the best quality components with rigorous engineering specifications. The result is a speaker that offers both durability and a superb sound. Especially for use in yachts, cruise ships or sauna’s... CMAR is available in 5 ¼ inch, 6 ½ inch and 8 inch, so that there is always a speaker that exactly fits your needs!

Superb sound and efficiency, even in humid environments.
5 1/4”woofer – 1” tweeter
50 Watts program power at 8 Ohm
Stylish but yet discrete
Can be used in temperatures up to 95°C
Sealing ring included for watertight mounting on flat surfaces.
Especially designed fully plastic basket that protects against vertically dropping liquids.
Stainless steel grille as an absolute guarantee against rust, plastic chassis.
8 Ohm voice coil allows connecting up to 2 APart CMAR speakers to a 4 Ohm stable amplifier channel.

[Manual >>](#)

[Technical sheet >>](#)