

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

## Biamp CMAR5 W - Plafonski zvučnik

---

Šifra: 6935

Kategorija proizvoda: Plafonski Zvučnici

Proizvođač: Biamp

**Cena: 7.320,00 rsd**

Biamp CMAR5 W - Plafonski zvučnik

White 5 “ build-in speaker for use in marine or very humid environments

Image not found or type unknown

[Click to enlarge picture](#)

Shape: round  
Rated RMS power: 25W  
Music power: 50W  
Impedance: 8 Ohm  
Frequency response: 100Hz to 20 KHz  
SPL 1W/1m in dB: 85dB  
Dispersion (at 1kHz, 2kHz, 4kHz, 8kHz in degrees): 180°,120°,120°  
HP filter build in: Yes, HP on tweeter  
Woofer size: 5 1/4 inch  
Tweeter size: 1 inch  
Color: white  
Chassis Type: plastic  
Grill material: stainless Steel  
IP classification: IP65  
Max operating temp: 95°C  
Removable grill: yes  
Fixing type: screws  
Cut Out dimensions: 110mm  
Outside dimensions: 152mm  
Mounting depth: 55mm  
Net Weight: 0.6kg  
Gross Weight: 0.8Kg

The APart CMAR5-W marine loudspeaker has been designed especially to offer quality sound even in the most difficult, humid and hot conditions. That’s why we have combined the best quality components with rigorous engineering specifications. The result is a speaker that offers both durability and a superb sound. Especially for use in yachts, cruise ships or sauna’s... CMAR is available in 5 ¼ inch, 6 ½ inch and 8 inch, so that there is always a speaker that exactly fits your needs!

Superb sound and efficiency, even in humid environments.  
5 1/4”woofer – 1” tweeter  
50 Watts program power at 8 Ohm  
Stylish but yet discrete  
Can be used in temperatures up to 95°C  
Sealing ring included for watertight mounting on flat surfaces.  
Especially designed fully plastic basket that protects against vertically dropping liquids.  
Stainless steel grille as an absolute guarantee against rust, plastic chassis.  
8 Ohm voice coil allows connecting up to 2 APart CMAR speakers to a 4 Ohm stable amplifier channel.

[Manual >>](#)

[Technical sheet >>](#)