

Biamp Apart MA 125 - 100V pojačalo

Biamp - Apart MA 125 - 100V pojačalo

Šifra: 2324

Kategorija proizvoda: 100V Pojačala

Proizvođač: Biamp - Apart

Cena: **52.680,00** rsd

The MA125 is a very compact, professional PA mixing amplifier for commercial and industrial applications. The MA125 can drive 8 Ohm or constant voltage loudspeakers.

The MA125 has 4 microphone inputs with integrated speech filters, 4 selectable line inputs and one emergency line / telephone input. MIC input 1 is meant to be the main microphone paging input. Its signal can be fed via the front jack or via the XLR3, DIN5 or Euroblock connector at the back. When needed, two APART paging microphones (MIC-PAT-D) can be wired in parallel on each microphone input.

The MA125 has a 3-level priority system. The emergency line / telephone input at the back has the highest priority. MIC1 has the second priority level and the third priority level can be activated by a dry contact at the back of the amplifier. This dry contact mutes all background music inputs. It also activates the integrated chime. The level of the chime can be adjusted at the back of the amplifier. Activation of the dry contact, releases a 24V output power? this can be used to switch the relays of loudspeaker attenuators or other devices.

When needed the signals mixed via your MA125 mixing amplifier can be recorded or distributed via the record output.

Further the MA125 is supplied with detachable 19" brackets.

Input : MIC1 (Front / Rear) : Bal. 1/4" Jack / Bal XLR, DIN5 (1.5mV), Euroblock. 14V phantom power via on-off switch at back panel

Input : MIC2-3-4 : XLR3 balanced (1.5 mV). 14V phantom power via on-off switch at back panel

Input

Input : AUX : RCA cinch (500 mV)

Input

Input : Tuner : RCA cinch (300 mV)

Input

Output Power RMS : Rated : 125 watt

Output

Output impedance : 50V (200Ohm) - 70V (39.2Ohm) - 100V (80Ohm) - 8 Ohm

Pre a

Record out : RCA cinch mono (1V)

Priori

Chime : 2-tone chime activated by contact closure on Euroblock or DIN5. Volume adjustable

closeH
(200

Priority system : Level 2: VOX Mute : On MIC 1 (0.6 mV), mutes mic 2,3 & 4 and line inputs. Level set by trimmer

Priori
inputs

Limiter : Dynamic limiter -3dB

Frequ

S/N Ratio : Amplifier : Better than 95 dB, 22 Hz - 22 kHz

S/N R

S/N Ratio : Mic : Better than 70 dB, 22 Hz - 22 kHz

Disto

Bass control : ± 10 dB, 100 Hz

Treble

Power supply : 230 / 115 V DC or 24V DC

Dime