

Biamp MASK8F BK - Nazidni zvučnik

Šifra: 15533
Kategorija proizvoda: Outdoor Zvučnici
Proizvođač: Biamp

Cena: 38.280,00 **rsd**

mask8f has a very powerful 8" coated paper cone woofer. Together with the Ferro-fluid cooled silk dome tweeter on a Waveguide horn, this results in a high SPL, an ultra-low distortion and a sound that comes close to studio monitor quality. The built-in Auto-Reset 2-step Protection Guard together with the quality components makes MASK8F a fail-safe loudspeaker, even at high power loads! After mounting the bracket on the wall, the sleeve in the bracket makes it quite easy and safe to fix the MASK8F loudspeakers, even in uncomfortable positions. The cabinet has several thread mounting points tapped at the back, the top and side of the cabinet. This way the cabinet can be rigged or mounting clamps can be used. MASK8F is delivered with a metal U-Mounting bracket.

FEATURES

- High speech intelligibility coupled with full-range music reproduction
- Dome tweeter on waveguide horn for broad dispersion
- Equipped with eight rigging points
- Loudspeaker overload protection for 24/7 failsafe operation

TECHNICAL SPECIFICATIONS

Operating Mode	Passive
Operating Environment	Indoor
Operating Range (-10dB)	53 Hz to 22 kHz
Nominal Beamwidth (H x V)	100° x 100°

Biamp MASK8F BK - Nazidni zvučnik

mask8f has a very powerful 8" coated paper cone woofer. Together with the Ferro-fluid cooled silk dome tweeter on a Waveguide horn, this results in a high SPL, an ultra-low distortion and a sound that comes close to studio monitor quality. The built-in Auto-Reset 2-step Protection Guard together with the quality components makes MASK8F a fail-safe loudspeaker, even at high power loads! After mounting the bracket on the wall, the sleeve in the

Transducers	LF 1 x 8" (203 mm) coated paper cone HF 1 x 1" (25 mm) soft dome	
Continuous Power Handling @ Nominal Impedance	40V	200W @ 8W (800W peak)
Nominal Sensitivity @ 1m	@ 1W 87 dB	@ 2.83V 87 dB
Nominal Maximum SPL @ 1m	Peak 116 dB	Continuous 110 dB
Protection	2-step self-resetting protection	
Recommended Amplifiers	200W - 400W @ 8W (40V - 57V)	

PHYSICAL

Input Connection	(2x) Speakon™ connectors; (2x) 5-way binding posts
Mounting Provisions	U-bracket
Dimensions H x W x D	16.2" x 9.4" x 9.4" (411 mm x 250 mm x 250 mm)

Weight	19.8 lbs (9.0 kg)
Finish	Refer to the Technical Drawings (page 3)
Accessories (included)	U-brackets; safety cable

APPLICATIONS

Bars and Restaurants · Hotels · Casinos Retail Outlets · Health and Fitness Clubs Houses of Worship · Exhibit Halls Corporate Meeting Rooms

DESCRIPTION

The Desono MASK8F two-way, 8" surface mount loudspeaker delivers crystal clear sound for all your public address and background music needs. Available in black or white, its 8” coated paper cone woofer and 1” silk dome tweeter results in a high SPL and extremely low distortion, ensuring unprecedented clarity over the entire frequency spectrum.

The MASK8F is equipped with a 1.4" (35 mm) metal pole mount adapter on the bottom for mounting to loudspeaker stands.

The Desono MASK8F is an ideal choice for indoor distributed audio applications that demand superior speech intelligibility and full range music reproduction.

TECHNICAL DRAWING / DIMENSIONS / FINISH

H x W x D

16.2" x 9.4" x 9.4"

(411 mm x 250 mm x 250 mm)

Unit Weight

19.8 lbs (9.0 kg)

Shipping Weight

24.7 lbs (11.2 kg)

Grille:

Steel

White (RAL 9003) or Black (RAL 9011) finish

Enclosure / Finish

MDF, matte finish, White or Black

