Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Biamp MASK4CT-W - Nazidni zvučnik



Šifra: 12599
Kategorija prozivoda: Outdoor Zvučnici
Proizvođač: Biamp

Cena: 16.680,00 rsd

Complete with time saving innovative click mount system for quick and simple installation.
The MASK4CT background music loudspeaker benefits from a stylish innovative design and can be used in low impedance 16 ohms (up to 4 loudspeakers in parallel on a standard 4 ohms amplifier channel) or in 100 volt line systems. Power tappings of 20,10, 5 & 2.5 watts are selected via a rotary switch on the back.
The powerful 4.25" woofer and Ferro-fluid cooled 1" silk dome tweeter offers high SPL and ultra low distortion. The internal bracketing and shape of the cabinet avoids internal interference and optimises the sound quality.
Built in auto-reset overload protection - 3-step Protection Guard is effective even at high power loads!
Suitable for use either indoors or outdoors, supplied with wall mounting bracket and available in black or white.

Timeless design
Weather resistant (aluminium grille)
ClickMount: click & connect
Connectors with passthrough and 0.14 – 4 mm² solid or stranded wire capacity
Wall and ceiling mountable
Integrated spirit level
Unique 3 stage overload protection
Asymmetric tweeter horn design
Coated 4.25”LF driver for MASK4C(T)
Horn loaded silk dome tweeter
Paintable in any RAL color
Rotatable logo
70W power handling for MASK4C(T)
70V and 100V compatible
Integrated safety nut for SAFCAB (supplied)
The installer can mount the ClickMount and connect the speaker cables while the speakers are still safely packed inside the packing carton.
Glass fibre reinforced bracket included
Speakers designed to be used in combination with the included
ClickMount
Incorporated 5º downward listening angle

height	238 mm
width	144 mm

depth	144 mm
loudspeaker system	2-way
woofer size	4,25 inch
woofer cone material	coated paper
tweeter size	1 inch
mounting system	clickmount
100V transformer power taps	20 - 10 - 5 - 2.5 watts
70V transformer power taps	20 - 10 - 5 - 2.5 - 1.25 watts
impedance (ohms)	16
low impedance dynamic power	70 watts
ow impedance RMS power	50 watts
SPL 1W/1m	89 dB
max SPL 1m	104 dB
frequency response	80 - 20k Hz
main construction material	ABS plastic
grille main material	aluminium
IP rating	64
Horizontal dispersion angle 1000 Hz	180°
Vertical dispersion angle 1000 Hz	180°
Net weight product (kg)	1.85

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.