

## Biamp MPH31-G - Instalacioni zvučnik

Šifra: 8912

Kategorija proizvoda: Horn Zvučnici

Proizvođač: Biamp

**Cena: 11.280,00 rsd**

message loud and clear.

The MPH31-G has been designed especially for outdoor background music, but is also applicable on any other location where you may want to benefit from the sturdy housing and IP54 rating. This horn loaded music projector can operate in 30, 15, 7.5 and 4 watts in a 100 volt system by using the simple and easy accessible switch at the back of the speaker.

If you are looking for a solution for balanced sound for music and speech reproduction, the MPH31-G will definitely come out as a well appreciated loudspeaker with lots of possibilities. Installers simply love the fact that they don't need to open the cabinet to connect the speaker wires.

### Biamp MPH31-G Instalacioni zvučnik

## Horn loaded sound projector

The MPH31-G is a horn loaded sound projector suited for low impedance and 100 volt installations. The most common used applications are noisy areas where you need the sound to be more directive. It is for sure the ideal solution for production halls, warehouses... Be sure everyone heard your

|                                   |                         |                    |              |
|-----------------------------------|-------------------------|--------------------|--------------|
| outside diam.                     | 0 mm                    | height             | 170 mm       |
| width                             | 226 mm                  | depth              | 244 mm       |
| loudspeaker system                | single cone             | woofer size        | 5,25 inch    |
| woofer cone material              | paper                   | mounting system    | U-bracket    |
| 100V transformer power taps       | 30 - 15 - 7,5 - 4 watts | impedance          | 8 ohms       |
| low impedance dynamic power       | 30 watts                | SPL 1W/1m          | 92 dB        |
| max SPL 1m                        | 107 dB                  | frequency response | 120 - 15K Hz |
| main construction material        | ABS plastic             | IP rating          | 54           |
| applicable low impedance          | Yes                     | applicable in 100V | Yes          |
| Vertical dispersion angle 1000 Hz | 180°                    |                    |              |