

Biamp REVAMP 4120T - 100V pojačalo

Šifra: 375
Kategorija proizvoda: 100V Pojačala
Proizvođač: Biamp

Cena: 143.880,00 rsd

bridged dual mono or bridged stereo systems. This amplifier contains an intelligent variable speed cooling fan that only will be activated in case of emergency.

In order to match each input to its respective source the input sensitivity can be adapted to your needs. The input stage also features a build-in 250 Hz HP-filter to optimise the system for use on horn speakers whenever you would need this. Each pair of outputs can be bridged to give you 2 x 240 watts of output power!

The very intuitive front display shows what is going on with one blink of an eye. The output power is constantly under control thanks to our own made limiter that prevents annoying pumping limiter sound but yet keeps the system fully under control and you still have that dynamic sound.

Ease of use, high-tech, reliability and a wide versatility has never been as cleverly combined as in this REVAMP4120T amplifier.

Biamp REVAMP 4120T - 100V pojačalo

REVAMP4120T is a professional 4-channel digital power amplifier with 4 x 120 watts output power @ 100 volt (or @ 4 ohms), but the unit is also bridgeable to 2 x 240 watts @ 100 volt (or @ 4 ohms). The unit incorporates a high efficient SMPS power supply, outputs with efficient Class D output topology and output transformers.

REVAMP4120T is the ideal amplifier for applications with 4 zones in mono, 2 zones in stereo or even

19" (483 mm wide) rack mounting	Yes	height- rack units (1U=44 mm)	2 U
depth (build in)	330 mm	depth (incl front)	338 mm
power supply	115 - 230 VAC volts	Power supply technology	switching mode power supply
power consumption (max)	525 watts	output power RMS 100 volts	4 x 120 watts
output power RMS 4 ohms	4 x 120 watts	output power RMS 8 ohms	4 x 60 watts
output power RMS bridged	2 x 240 watts	minimum impedance load	4 ohms
output voltage tapings	100 -70 - 50 - 35 - 4 Ohm watts	output channels	4
line input balanced	4	line input unbalanced	4
Channel separation	> 68 dB @ 1 kHz	Power amp topology	Class-D
frequency response (in Hz)	50 - 20K	cooling system	fan
applicable in 100V	Yes	applicable low	Yes