Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Biamp REVAMP 4240T - 100V pojačalo



Šifra: 10058
Kategorija prozivoda: 100V Pojačala
Proizvođač: Biamp

Cena: 179.880,00 rsd

REVAMP4240T is the ideal amplifier for applications with 4 zones in mono, 2 zones in stereo or even bridged dual mono or bridged stereo systems. This amplifier contains an intelligent variable speed cooling fan that only will be activated in case of emergency.
In order to match each input to its respective source the input sensitivity can be adapted to your needs. The input stage also features a build-in 250 Hz HP-filter to optimise the system for use on horn speakers whenever you would need this. Each pair of outputs can be bridged to give you 2 x 480 watts of output power!
The very intuitive front display shows what is going on with one blink of an eye. The output power is constantly under control thanks to our own made limiter that prevents annoying pumping limiter sound but yet keeps the system fully under control and you still have that dynamic sound.
Ease of use, high-tech, reliability and a wide versatility has never been as cleverly combined as in this REVAMP4240T amplifier.

dynamic output power 4 ohms 4 x 240 watts
RMS output power 4 ohms 4 x 240 watts
dynamic output power 8 ohms 4 x 120 watts
RMS output power 8 ohms 4 x 120 watts
dynamic output power bridged 8 ohms 2 x 480 watts
output power RMS bridged 8 ohms 2 x 480 watts
output power RMS 100 volts 4 x 240 watts
output power RMS bridged 100 volts 2 x 480 watts
minimum impedance load per channel 4 ohms
minimum impedance load bridged per channel 8 ohms
power consumption (max) 1050 watts
19" (483 mm wide) rack mounting Yes
height- rack units (1U=44 mm) 2 U
depth (build in) 330 mm
depth (incl front) 338 mm
power supply 115 - 230 VAC volts
Power supply technology 2 x switching mode power supply
output voltage tappings 100 - 70 - 50 - 35 - 4 Ohm watts
output channels 4
line input balanced 4
line input unbalanced 4
Channel separation > 68 dB @ 1 kHz
Power amp topology Class-D
frequency response (in Hz) 50 - 20K
cooling system fan
applicable in 100V Yes
applicable low impedance Yes
Net weight product (kg)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.