

## Biamp REVAMP 4240T - 100V pojačalo

Šifra: 10058  
Kategorija proizvoda: 100V Pojačala  
Proizvođač: Biamp

**Cena: 179.880,00 rsd**

of outputs can be bridged to give you 2 x 480 watts of output power!  
The very intuitive front display shows what is going on with one blink of an eye. The output power is constantly under control thanks to our own made limiter that prevents annoying pumping limiter sound but yet keeps the system fully under control and you still have that dynamic sound.  
Ease of use, high-tech, reliability and a wide versatility has never been as cleverly combined as in this REVAMP4240T amplifier.

dynamic output power 4 ohms 4 x 240 watts  
dynamic output power 8 ohms 4 x 120 watts  
dynamic output power bridged 8 ohms 2 x 480 watts  
watts  
output power RMS 100 volts 4 x 240 watts  
watts  
minimum impedance load per channel 4 ohms  
8 ohms  
power consumption (max) 1050 watts  
height- rack units (1U=44 mm) 2 U  
depth (incl front) 338 mm  
Power supply technology 2 x switching mode power supply  
Ohm watts  
output channels 4  
line input unbalanced 4  
Power amp topology Class-D  
cooling system fan  
applicable low impedance Yes

### Biamp REVAMP 4240T - 100V pojačalo

REVAMP4240T is the ideal amplifier for applications with 4 zones in mono, 2 zones in stereo or even bridged dual mono or bridged stereo systems. This amplifier contains an intelligent variable speed cooling fan that only will be activated in case of emergency.

In order to match each input to its respective source the input sensitivity can be adapted to your needs. The input stage also features a build-in 250 Hz HP-filter to optimise the system for use on horn speakers whenever you would need this. Each pair

RMS output power 4 ohms 4 x 240 watts  
RMS output power 8 ohms 4 x 120 watts  
output power RMS bridged 8 ohms 2 x 480

output power RMS bridged 100 volts 2 x 480

minimum impedance load bridged per channel

19" (483 mm wide) rack mounting Yes  
depth (build in) 330 mm

power supply 115 - 230 VAC volts  
output voltage tapings 100 - 70 - 50 - 35 - 4

line input balanced 4  
Channel separation > 68 dB @ 1 kHz  
frequency response (in Hz) 50 - 20K  
applicable in 100V Yes  
Net weight product (kg)