

ART PRO AUDIO HeadAmp6 Pro

ART PRO AUDIO HeadAmp6 Pro

Šifra: 291  
Kategorija proizvoda: Pojačala za Slušalice  
Proizvođač: ART

Cena: 39.000,00 rsd

The ART HeadAmp6PRO is a six-channel stereo headphone amplifier that includes a six-channel auxiliary input section that can be used to provide the popular "More-Me" function on each headphone mix. Each output channel also features a dual function BALANCE control which will pan between LEFT & RIGHT sides of the main signal bus, or vary the MIX between the main signal bus and the AUXILIARY input for that respective channel.

Bass and treble controls are included on each output channel for fine-tuning the tone. Outputs include both front and rear panel stereo 1/4-inch TRS jacks for ease of installation and quick patching capability. Two MONO select buttons on each channel select between four operating modes; 1) Stereo, 2) Mono Left, 3) Mono Right, 4) Mono Both (Left & Right) for versatile monitoring solutions.

The main outputs for each channel of the headphone amplifier are rear mounted stereo TRS jacks and are wired in parallel with the corresponding output jacks on the front panel. Front panel, rear panel, or both front and rear panel outputs can be used simultaneously to drive headphones or be used as feeds to additional headphone amplifiers in a distributed audio network.

Input options include XLR and 1/4-inch TRS balanced inputs with matching "Thru" jacks for bridging multiple HeadAmp 6 Pro units. An additional front panel stereo 1/4-inch TRS jack for quick patch override of the rear panel inputs is included for quick insertion of any stereo source. Eight-segment LED level indicators provide visual feedback of the signal level on all channels as well as the main signal bus.

## Features

Six Channels with Separate Bass & Treble Controls	Front & Rear Panel Output Jacks	XLR
	Operates in Stereo, Mono (Source Left), Mono (Source Right) or Summed Mono (Source Left & Right)	Auxiliary Input
	8-Sement LED Level Indicators on all Channels & Bus	

## Specifications

Maximum Input Level: +21.5dBu	Input Impedance: 40k ohm Balanced	Maximum Output Power: 100W per channel
-------------------------------	-----------------------------------	--

32ohms

**Maximum Gain:** 25.6 dB (Tone Controls Set Flat)

**CMMR:** 40dB

**Weight:** 6.8 lbs (3.1 kg)

**Freq**  
2dB  
**Dim**  
x 19  
**Pow**  
Hz