

ART PRO AUDIO Tube MP Project Series

Šifra: 00293
Kategorija proizvoda: Studijska Pretpojačala
Proizvođač: ART

Cena: 14.280,00 rsd

circuitry, we have improved virtually every aspect of our already successful Tube MP series. With up to 70dB of clean musical gain and high output signal drive capability the cold digital world will melt with your mixes! Charge up your creativity with the Tube MP Project Series!

Optional ART SM1 stand mount securely attaches the Tube MP Project Series to any microphone stand for live stage or studio applications is available.

Features

- Extremely Low Noise Discrete Front End
- High Output Signal Drive Capability
- Switch Selectable Input Impedance
- Built-in Low Noise Phantom Power Supply
- XLR and 1/4" Inputs and Outputs
- High Cut Filter Switch

- Up to 70dB of Clean, "Musical" Gain
- Fast FET Limiter to Prevent Overload
- Precision LED Metering
- Compact, Stackable all Aluminum Chassis
- Phase Invert Switch
- Variable Input and Output Controls

Specifications

Frequency Response: 10Hz to 40kHz, +/-1 dB (typical)

CMRR: > 60dB (typical)

Equivalent Input Noise:

Input/Output Connections: Input: 1/4" TRS unbalanced (1meg Ohm), XLR female balanced. Output: 1/4" TRS unbalanced (600 Ohm), XLR male balanced (

Input Gain Pad: Switchable, 20dB

Total Harmonic Distortion: <0.05% (typical)

Dynamic Range: > 100dB (20Hz to 20kHz)

Input Impedance: Switchable, 4.7k Ohms / 600 Ohms (XLR)

Maximum Gain: 70dB (XLR - XLR), +50dB (1/4" - XLR)

Maximum Input Level: +17dBu (1/4"), +16dBu (XLR)

ART PRO AUDIO Tube MP Project Series

The Tube

MP Project Series is a professional quality audio interface that lets you connect microphone, instrument, and line level signals to a mixer or other audio input. This hybrid design is the latest in a long line of ART tube preamps. We took our legendary Tube MP series and updated every aspect of the design, inside and out, while still maintaining a compact, reliable, and cost effective product. From the new all-aluminum stackable chassis to the precision LED level metering

circuitry, we have improved virtually every aspect of our already successful Tube MP series. With up to 70dB of clean musical gain and high output signal drive capability the cold digital world will melt with your mixes! Charge up your creativity with the Tube MP Project Series!

Optional ART SM1 stand mount securely attaches the Tube MP Project Series to any microphone stand for live stage or studio applications is available.

Features

- Extremely Low Noise Discrete Front End
- High Output Signal Drive Capability
- Switch Selectable Input Impedance
- Built-in Low Noise Phantom Power Supply
- XLR and 1/4" Inputs and Outputs
- High Cut Filter Switch

- Up to 70dB of Clean, "Musical" Gain
- Fast FET Limiter to Prevent Overload
- Precision LED Metering
- Compact, Stackable all Aluminum Chassis
- Phase Invert Switch
- Variable Input and Output Controls

Specifications

Frequency Response: 10Hz to 40kHz, +/-1 dB (typical)

CMRR: > 60dB (typical)

Equivalent Input Noise:

Input/Output Connections: Input: 1/4" TRS unbalanced (1meg Ohm), XLR female balanced. Output: 1/4" TRS unbalanced (600 Ohm), XLR male balanced (

Input Gain Pad: Switchable, 20dB

Total Harmonic Distortion: <0.05% (typical)

Dynamic Range: > 100dB (20Hz to 20kHz)

Input Impedance: Switchable, 4.7k Ohms / 600 Ohms (XLR)

Maximum Gain: 70dB (XLR - XLR), +50dB (1/4" - XLR)

Maximum Input Level: +17dBu (1/4"), +16dBu (XLR)

Maximum Output Level: +20dBu (1/4"),
+26dBu (XLR)

Output Phase: Switchable, Normal/Invert

Phantom Power: Switchable, +48V DC,
filtered, current limited

Chassis Type: Aluminum Anodized with
integral/stackable rubber sides

Tube Type: 12AX7A hand selected

Weight: 2.5 lbs (1.14 kg)

Low Cut Filter: Switchable, -3dB @ 40Hz

Output Limiter Type: Switchable, Fast &
Musical FET Limiter, > 20dB limit range

Signal Metering: Precise LED array with a
fast attack and moderate release

Power Requirements: 10VAC @ 700mA
(typ)

Dimensions: 6.5"D x 5.9" W x 1.75" H
(165mm x 150mm x 44.5mm)