Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

ART PRO AUDIO TUBE MP Studio V3 - Instrumentalno pretpojačalo



Šifra: 00286
Kategorija prozivoda: Studijska Pretpojačala
Proizvođač: ART

Cena: 17.880,00 rsd

The Tube MP Studio V3 delivers warmth and fatness to any audio source while maintaining an exceptionally low-noise signal path. While its primary function is as a microphone preamp with +48V phantom power, variable gain and phase reverse switching, the Tube MP is also an exceptionally versatile tube driven direct box for any instrument source.

The Tube MP Studio V3 uses ART's proven V3™ (Variable Valve Voicing) Technology to instantly contour the tone to any source. V3™ presets were created and fine-tuned by some of the industry's top studio and live-sound engineers and allow instant access to a multitude of preamp settings designed for guitars (electric and acoustic), keyboards, bass guitars, drums, vocals and more. Additionally, the Tube MP Studio V3 employs OPL™ (Output Protection Limiting) technology to protect the next component in your signal path from clipping and overloads.

The Tube MP Studio V3 offers exceptional sound quality and superior performance to that typically found in "on-board" preamps found in today's low-cost mixers, multi-track recorders and audio cards making it an ideal tone-shaping tool for any application.

Features

- Provides Superior Preamplification for: Microphones, Instruments and Line Level Sources
- V3™ - Variable Valve Voicing
- OPL™ - Output Protection Limiting
- Hand Selected 12AX7A Provides 70dB of Gain Smooth, Warm and Fat Sound Quality
- Variable Input and Output Gain Controls
- Excellent as a Tube DI
- XLR and 1/4" Inputs and Outputs
- +48 Volts of Phantom Power
- Phase Reversal Switch
- Portable, All Steel Construction

Specifications

- **Frequency Response**: 5Hz to 50kHz (+0 to -1dB)
- **Total Harmonic Distortion**: <.01% (clean); 0.1% (warm)
- **CMMR**: > 75dB (typ. @ 1kHz)
- **Dynamic Range**: <100dB
- **Equivalent Input Noise**: -129dBu (A weighted, xlr to xlr)
- **Maximum Gain**: 80dB (xlr to xlr); 74dB (1/4" to xlr)
- **Maximum Input Level**: +19dBu (xlr); +22dBu (1/4")
- **Maximum Output Level**: +28dBu (xlr); +22dBu (1/4")
- **Phantom Power**: +48 volts
- **Power Requirements**: 110-125 VAC, 16W
- **Tube Type**: 12AX7A - Dual Triode (Hand Selected)
- **Dimensions**: 5.0"D x 5.5"W x 2.0" H
- **Weight**: 1.5 lbs

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.