

ART PRO AUDIO TUBE MP Studio V3 - Instrumentalno prepojačalo

Šifra: 286

Kategorija prozivoda: Studijska Prepojačala

Proizvođač: ART

Cena: 19.800,00 rsd

contour the tone to any source. V3™ presets were created and fine-tuned by some of the industry's top studio and live-sound engineers and allow instant access to a multitude of preamp settings designed for guitars (electric and acoustic), keyboards, bass guitars, drums, vocals and more. Additionally, the Tube MP Studio V3 employs OPL™ (Output Protection Limiting) technology to protect the next component in your signal path from clipping and overloads.

The Tube MP Studio V3 offers exceptional sound quality and superior performance to that typically found in "on-board" preamps found in today's low-cost mixers, multi-track recorders and audio cards making it an ideal tone-shaping tool for any application.

ART PRO AUDIO TUBE MP Studio V3 - Instrumentalno prepojačalo

MP Studio V3 delivers warmth and fatness to any audio source while maintaining an exceptionally low-noise signal path. While its primary function is as a microphone preamp with +48V phantom power, variable gain and phase reverse switching, the Tube MP is also an exceptionally versatile tube driven direct box for any instrument source.

The Tube MP Studio V3 uses ART's proven V3™ (Variable Valve Voicing) Technology to instantly

Features

Provides Superior Preamplification for:
Microphones, Instruments and Line Level
Sources

OPL™ - Output Protection Limiting
Variable Input and Output Gain Controls
XLR and 1/4" Inputs and Outputs
Phase Reversal Switch

V3™ - Variable Valve Voicing

Hand Selected 12AX7A Provides 70dB of Gain
Smooth, Warm and Fat Sound Quality
Excellent as a Tube DI
+48 Volts of Phantom Power
Portable, All Steel Construction

Specifications

Frequency Response: 5Hz to 50kHz (+0 to -1dB)

Total Harmonic Distortion: <.01% (clean); 0.1% (warm)

CMMR: > 75dB (typ. @ 1kHz)

Dynamic Range: <100dB

Equivalent Input Noise: -129dBu (A weighted, xlr to xlr)

Maximum Gain: 80dB (xlr to xlr); 74dB (1/4" to xlr)

Maximum Input Level: +19dBu (xlr); +22dBu (1/4")

Maximum Output Level: +28dBu (xlr); +22dBu (1/4")

Phantom Power: +48 volts

Power Requirements: 110-125 VAC, 16W

Tube Type: 12AX7/A - Dual Triode (Hand Selected)

Dimensions: 5.0"D x 5.5"W x 2.0" H

Weight: 1.5 lbs

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.