

ISO ACOUSTIC GAIA III

ISO ACOUSTIC GAIA III

Šifra: 13691
Kategorija proizvoda: Ostalo
Proizvođač: IsoAcoustics

Dimensions (W x H): 1.7" x 1.5" (43mm x 39mm)
Maximum weight: 70lbs (32kg) per set of 4
Quantity: 4 per box
Thread sizes included: M6-1.0, M8-1.25 and ¼"-20

Cena: 23.880,00 rsd

How to install GAIA III isolators

Optimal results are achieved by installing the GAIA isolators with the logo facing the listening position, or rotated 180 degrees, to align the isolators with the speaker's motive forces. The GAIA III provides a high degree of isolation while resisting lateral movement and oscillations to maintain alignment with the listening position. Lift and place the speakers into position as the GAIA lower isolators will adhere to the supporting surface.

The GAIA's are threaded into the base of the speaker or subwoofer to replace the existing spikes or feet. Threading the GAIA's into the base of the speaker creates a strong connection with the speaker. With the top of the GAIA housing connected with the speaker and the bottom of the GAIA connected to the supporting surface, all of the energy is then managed by the GAIA's internal isolator.

The GAIA III includes thread adaptors for sizes M6-1.0, M8-1.25 and ¼"-20. Alternative thread size adaptors are available upon request through IsoAcoustics distributors.