

## FOCAL 100 OD 8 White

image not found or type unknown

## FOCAL 100 OD 8 White

Šifra: 13846

Kategorija proizvoda: Outdoor Zvučnici

Proizvođač: Focal

**Cena: 29.880,00 rsd**

*\*Dimensions with brackets: 10.2"x11"x15.4"*

*\*\*Established by the [International Electrotechnical Commission \(IEC\)](#), IP codes are international standards used to identify the degrees of protection of products against the ingress of solid or liquid foreign objects. The first digit of the IP code represents the level of protection against the ingress of solid foreign objects, such as dust (0 to 6). The second digit represents the level of protection against harmful ingress of water (0 to 8).*

### FOCAL TECHNOLOGIES

An aluminium inverted dome tweeter for excellent sound dispersion; bass/mid-range speaker driver with a waterproof Polypropylene cone and [Polyglass](#) treatment for perfect definition: the 100 OD8 loudspeaker features high-performing "made in Focal" components that all have a part to play in the sharing and experience of the Focal sound. 100 OD8 delivers a slightly higher efficiency and a power handling to 100 OD6, allowing configurations with higher volume.

### COMPLEMENTARITY

With its high impedance (8 ohms), the 100 OD8 loudspeaker offers the possibility of connecting two loudspeakers in parallel on the same amplifier output.

### EASY TO INSTALL AND USE

100 OD8 is equipped with a reinforced, notched assembly bracket made from solid, anti-rust Aluminium, and offers the option to rotate the loudspeaker 180 degrees for unbeatable sound diffusion. The product is therefore easier to install, as well as to position, either vertically or horizontally, depending on your preference and the layout of your outdoor space.

Key points • Technical design, IP66 certified (water and dust) • Ready-to-paint grille and cabinet • 8 ohms impedance, possibility to connect 2 loudspeakers to the same amplifier output

Type Outdoor loudspeaker Speakers Aluminum inverted dome tweeter 8" (210mm) waterproof woofer with Polyglass treatment Sensitivity (2,83V/1m) 88dB Frequency response (+/-3dB) 60Hz-23kHz Low frequency point (-6dB) 45Hz Nominal impedance 8Ω Minimal impedance 6.7Ω Recommended amp power 20-150W Filtering frequencies 2,800Hz Dimensions (L x P x H) with brackets 10.2 x 11 x 15.4" (258 x 280 x 390mm) Net weight with brackets 12.6lbs (5.8kg)