logo not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

DAS AUDIO Avant 15A - Aktivni zvučnik

DASEAUDIO Avante 15 AnovAktivni zvučnik

Powered 2-way System
1 x 15\" + 1\" Driver
Biamp 500 W LF + 100 W HF

Šifra: 4698

Kaeeuুপ্রের prozivoda: Aktivne Zvučne Kutije

Proizvođač: DAS Audio

Cena: 119.880,00 rsd

- -Compact full-range system
- -Ultra lightweight 3rd generation Class D amplifier
- -Switch-mode power supply
- -Reduced size and weight
- -Pole mount socket

-Rigging points

The Avant series incorporates an impressive battery of high tech features that take powered portable systems to a new level of performance. The latest in Class D power amplification, digital signal processing and optimized D.A.S. components have been combined with enclosures designed for ease of transportation and road worthiness.

The 600 W Class D amplifier provides extended bandwith, improved dynamic range and exceptionally low distortion. This makes the Avant series one of the best sounding systems on the market. After all, isn't quality sound what it's all about?

The Digital Signal Processsing (DSP) incorporated in the Avant series provides unparalleled control over the audio signal. Critical parameters have been fine tuned for each cabinet, yet their consistent sound \"signature\" allows them to perform seamlessly with other systems from the Avant family.

The 15AV4 loudspeaker designed and built by D.A.S. provides powerful low frequency reproduction. High frequencies are handled by the M-50N compression driver which uses a neodymium magnet structure and 2\" titanium diaphragm for exceptional perormance in all types of applications.

Features		
Technical Data		
Nominal LF Amplifier Power	500 W	
Nominal HF Amplifier Power	100 W	
Frequency Range (-10 dB)	45 Hz-20 kHz (EQ Flat)	
Rated Peak SPL at 1 m	133 dB	
Dispersion	80ºH x 50ºV rotatable horn	
Enclosure Material	Plywood	
Color/Finish	Black/Paint	
Connectors	Input: Female XLR-Jack combo Loop Thru: XLR AC Input Male IEC	
AC Requirements	115 V, 50/60 Hz 230 V, 50/60 Hz	
Dimensions (H x W x D)	83 x 44.8 x 47.6 cm 32.7 x 17.6 x 18.7 in	
Weight	30 kg (66 lb)	