

FOCAL 100 OD 6 White

Šifra: 13883
Kategorija proizvoda: Outdoor Zvučnici
Proizvođač: Focal

Cena: 17.880,00 rsd

FOCAL 100 OD 6 White

THE HIGH-FIDELITY SOUND IS MOVING OUTDOORS
THE LOUDSPEAKER THAT STANDS UP TO ALL
WEATHERS!

In addition to its UV-treated, high-density
Polypropylene damping cabinet, the 100 OD6*
loudspeaker is IP66 certified** (Ingress Protection

rating 66). This reference international standard demonstrates the remarkable resistance of products to extreme weather conditions, and more specifically their watertight and dust-proof qualities. Integrating Focal Technologies, the 100 OD6 loudspeaker delivers the Focal's high-fidelity sound outdoors. It is also easy to install, thanks to its reinforced, notched assembly bracket. Its 180-degree rotation system makes it easy to position, too. And because, at Focal, attention is paid to each and every detail and to satisfying every taste, the grille and cabinet are available in black finish or white ready-to-paint finish.

FOCAL TECHNOLOGIES

An aluminium inverted dome tweeter for excellent sound dispersion; bass/mid-range speaker driver with a waterproof Polypropylene cone and Polyglass treatment for perfect definition: the 100 OD6 loudspeaker features high-performing components that all have a part to play in the sharing and experience of the Focal sound.

COMPLEMENTARITY

With its high impedance (8 ohms), the 100 OD6 loudspeaker offers the possibility of connecting two loudspeakers in parallel on the same amplifier output.

EASY TO INSTALL AND USE

100 OD6 is equipped with a reinforced, notched assembly bracket made from solid, anti-rust Aluminium, and offers the option to rotate the loudspeaker 180 degrees for unbeatable sound diffusion. The product is therefore easier to install, as well as to position, either vertically or horizontally, depending on your preference and the layout of your outdoor space.

- Speakers: 61/2" (165mm)	Aluminum inverted dome tweeter
	waterproof woofer with Polyglass treatment
- Sensitivity:	(2,83V/1m) 87dB
- Frequency response:	(+/-3dB) 65Hz-23kHz
- Low frequency point:	(-6dB) 55Hz
- Nominal impedance:	8Ω
- Minimal impedance:	6.7Ω
- Recommended amp power:	20-120W
- Filtering frequencies:	2,800Hz
- Dimensions: (L x P x H) with brackets	8.8 x 10.1 x 12.6" (224 x 256 x 319mm)

- Net weight with brackets:

9lbs (4.1kg)