

MOTU M2

Šifra: 13935
Kategorija prozivoda: USB Zvučne kartice
Proizvođač: MOTU

Cena: 31.080,00 rsd

BEST

AUC

Equipped with the ESS S-Master circuit, the M2 offers the best possible sound quality. The M2's unique circuit design provides the best possible sound quality, with a clarity and depth that is unmatched by any other USB interface.

- ESS S-Master
- The best sound quality
- Measured
- Measured
- ESS-cards

BEST IN CLASS

Speed

The M2 provides best-in-class speed for monitoring live inputs (mic, guitar or keyboard) through your computer, thanks to MOTU's expertly engineered USB drivers, which deliver class-leading, ultra-low 2.5 ms Round Trip Latency (at 96 kHz with a 32 sample buffer).



Metering

When recording and mixing, nothing is more critical than achieving optimum levels. The M2 is the only audio interface in its class with a full color LCD featuring clear, detailed level meters for all inputs and outputs. Enjoy professional-level volume control and feedback to get your sound just right.

LIVE STREAMING

Loopback

The M2 driver provides convenient loopback channels to your host computer, so you can easily route computer output back to the computer, where you can mix it with live mics and/or guitar inputs from the M2 in your host software for live streaming or podcasting. Streaming and podcasting has never been easier and better-sounding!

TECH SPECS

Technical Specifications

Sample rates	44.1, 48, 88.2, 96, 176.4, 192 kHz
Mic/line/guitar inputs	2 x XLR/TRS "combo jack" mic/line/Hi-Z guitar inputs Independent preamp gain, 48V phantom power and monitor switch for each input
Analog outputs	2 x 1/4" TRS line out (balanced, DC coupled) 2 x RCA (unbalanced) analog out (mirrored) 1 x 1/4" TRS stereo headphone
Computer I/O	1 x USB-C (compatible with USB Type A) 2.0 audio class compliant
MIDI I/O	1 x MIDI IN 1 x MIDI OUT 16 MIDI channels to/from computer host
Headphone	1 x 1/4" TRS stereo phone

Phantom power | 2 x individual +48V

Front panel	1 x 1/4" TRS headphone output 2 x XLR/TRS combo inputs 1 x potentiometer • monitor vol 1 x potentiometer • phone vol 2 x potentiometer • mic/instr input gain 4 x switches • (2) 48V and (2) MON 160 x 120 pixel full-colored LCD with input and output level meters
Power	Bus-powered through USB
Dimensions and weight	(width x depth x height, enclosure only) 7.5 x 4.25 x 1.75 inches 19.05 x 10.8 x 4.5 cm 1.35 lbs / 0.61 kg

System Requirements

Mac System Requirements	1 GHz Intel-based Mac or faster 2 GB RAM; 4 GB or more recommended macOS version 10.11 or later (Optional driver requires 10.13 or later) Available USB port A large hard drive (at least 500 GB for recording)
Windows System Requirements	1 GHz Pentium-based PC compatible or faster 2 GB RAM; 4 GB or more recommended Windows 7, 8 or 10 Available USB port A large hard drive (at least 500 GB for recording)
Class-Compliant Support	USB audio class compliant for plug-and-play operation on Mac or iOS (no driver required)
Included Software	MOTU Performer Lite Ableton Live 10 Lite 6GB of loops and sounds from Big Fish Audio, LucidSamples, Loopmasters and MOTU

Analog I/O

	Connector type	Dynamic range (A-weighted)	THD+N (unweighted)	Max level
Line Output	1/4" TRS, balanced, tip hot	120dB	-110dB	+16dBu

