

# MARTIN AUDIO Blackline XP15 Black - Aktivni zvučnik

Šifra: 13948  
Kategorija proizvoda: Aktivne Zvučne Kutije  
Proizvođač: Martin Audio

Cena: 173.880,00 rsd

MARTIN AUDIO Blackline XP15 Black - Aktivni zvučnik

**Featuring a 15" (380mm)/3" (75mm) voice coil LF drive unit, and a 1" (25mm) exit HF compression driver with a 1.75" (44mm) polyimide diaphragm. With an accurately-defined 80° x 50° coverage pattern, it combines very high output capability with exceptional sonic performance and low frequency impact.**

Its Class D amplifier module delivers 1000W LF + 300W HF peak output to the drivers, which are independently protected by RMS and peak limiters. Onboard DSP functions are controlled by a rotary encoder interface and multi-function, easy-to-use colour display on the rear panel. DSP features include crossover function, a three-channel mixer with three- band EQ on each input channel and a choice of three voicing presets and operating modes for flexible operation without external processing.

The symmetrical, multi-angle enclosure is manufactured from birch and poplar plywood and finished in textured black paint. It is fitted with M8 inserts for eyebolt suspension plus a pole-mount socket with a removable cap. Its cloth-backed protective steel grille is a spring-fit into the sides of the enclosure for easy access to rotate the HF horn.

ACOUSTICS	
TYPE	High output, self-powered two-way system
FREQUENCY RESPONSE (5)	55Hz - 20kHz ±3dB -10dB @ 45Hz
DRIVERS	LF: 15" (380mm)/3" (75mm) voice coil ferrite motor system HF: 1" (25mm) exit/1.7" (44mm) voice coil, polyimide dome compression driver
MAXIMUM SPL (9)	125dB continuous / 131dB peak
DISPERSION	80° H x 50° V (user-rotatable)
CROSSOVER	2kHz active, 24dB/octave
MODULE AUDIO IN/OUT	

INPUT CONNECTORS	2 x female XLR/ 1/4" jack combo
MIC/LINE INPUT IMPEDANCE	8 kΩ balanced
1/4" JACK TS INPUT IMPEDANCE	1 MΩ unbalanced
MIX OUTPUT CONNECTOR	1 x male XLR
MIX OUTPUT IMPEDANCE	600Ω balanced
INTERNAL PROCESSING	
INPUT CHANNEL EQ	3-band on each channel plus HPF (Ch1/2)
SPEAKER EQ	3 speaker mode/voicing presets
PROTECTION	LF and HF Peak and RMS limiting, amplifier thermal protection
AMPLIFIER MODULE	
TYPE	2 channel switch-mode, class D
PEAK OUTPUT POWER	1300W total 1000W LF, 300W HF
AVERAGE EFFICIENCY	89%
COOLING	External convection cooled
MAXIMUM AMBIENT TEMPERATURE	35°C (95°F) for full output
POWER SUPPLY	
TYPE	Switch-mode, fixed frequency with PFC
AC INPUT OPERATING RANGE	100-240V ~ AC, 50 - 60Hz
POWER FACTOR	> 0.98
NOMINAL POWER CONSUMPTION	550W Max
MAINS CONNECTOR	3-pin IEC
MECHANICAL	
ENCLOSURE	Multi-angle birch/poplar ply
FINISH	Black textured paint
PROTECTIVE GRILLE	Black perforated steel with scrim cloth backing

FITTINGS	13 x M8 inserts, pole-mount socket, 2 x pocket handles
DIMENSIONS	(W) 427mm x (H) 690mm x (D) 407mm (W) 16.8in x (H) 27.2 x (D) 16.0in
WEIGHT	26kg (57lbs)

### **Martin Audio XP15**

The loudspeaker shall be a self-powered two-way system. Its transducers shall consist of a reflex-loaded 15" low frequency driver and a 1" exit high frequency compression driver mounted on a high frequency horn. The horn shall be user-rotatable to enable vertical, horizontal and stage monitor operation.

Horizontal dispersion shall be 80° and vertical dispersion shall be 50°. The on-axis frequency response shall be 55Hz-20kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 131dB peak at 1 metre.

The loudspeaker shall incorporate a two-channel Class D amplifier which shall deliver a total of 1300W peak output to the transducers. Onboard DSP shall perform crossover and limiter functions and incorporate a three-channel mixer. Mixer settings, operating mode and voicing presets shall be effected by a rotary encoder and display screen on the rear panel. Bluetooth control and streaming shall be available as an option. The power supply shall employ Power Factor Correction and operate from 100-240V, 50-60Hz AC.

Audio input connectors shall be female XLR type combined with a ¼" jack. The mix output shall be available on a male XLR type connector. The AC power connector shall be a 3-pin IEC connector.

The loudspeaker enclosure shall be constructed from multi-laminate plywood with a black textured coating and be fitted with a pole-mount socket, pocket handles and M8 threaded inserts for mounting accessories. The drivers shall be protected by a perforated steel grille with a cloth backing.

Dimensions (W x H x D) shall be 427mm x 690mm x 407mm (16.8in x 27.2in x 16.0in). Weight shall be 26kg (57lbs).

The loudspeaker shall be the Martin Audio XP15.