Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Biamp MA30 - 100V pojačalo

Šifra: 13968
Kategorija prozivoda: 100V Pojačala
Proizvođač: Biamp



Cena: 32.280,00 rsd

FEATURES
Single channel; 30 watts of continuous power
Supports 4Ω and 70V/100V outputs
Class D amplifier topology
Intuitive front and rear panels
Four priority levels for audio routing
24V priority output overrides local volume controls
Dedicated emergency input with mute all switch
Paging mic input with contact closure and chime
One mic/line level input with 48V phantom power
Two stereo inputs
Fanless operation
Internal universal power supply
Auto standby mode
Rack mountable (2RU) with optional accessory
CE marked, UL listed, and RoHS compliant

INPUTS
Number of Inputs
Emergency (line level with contact): 1
Paging Mic (mic level with contact): 1
Mic/Line (balanced): 1
Stereo Line (unbalanced): 2
Input Priority Levels: 4
Priority Input Contact: Yes
Chime: Yes
Tone Control: Yes
Wall Panel Controls: Yes
Music Level Control: Yes
Front Panel Indicators: Signal present, clipping, overload condition, emergency mode active, paging active, VOX active
Emergency Input
Nominal Input Sensitivity: 0 dBV (1 Vrms)
THD+N (Pre-Out, @ -6dB): < 0.5%
Frequency Response (-3dB): 100 Hz – 20 kHz
Input Impedance: 5 kW
Paging Mic
Nominal Input Sensitivity (Bal. Mic): -45 dBV (5.6 mVrms)
THD+N (Pre-Out, @ -6dB): < 0.4%

Frequency Response (-3dB):
Balanced Mic: 165 Hz – 20 kHz
Unbalanced, Balanced Line: 20 Hz – 20 kHz
Gain: -15 to +15 dB
Chime Length: 2 sec
Input Impedance: 2 kW
Mic
Nominal Input Sensitivity:
Balanced Mic: -45 dBV (5.6 mVrms)
Balanced Line: -12 dBV (250 mVrms)
Unbalanced Line: -12 dBV (250 mVrms)
THD+N (Pre-Out, @ -6dB): < 0.2%
Frequency Response (-3dB):
Balanced Mic: 165 Hz – 20 kHz
Unbalanced, Balanced Line: 20 Hz – 20 kHz Phantom Power (balanced only): +48VDC (7mA/input) VOX
Attenuation (Mic, Inputs 1-2): 30 dB
Input Impedance: 2 kW
Inputs 1-2
Nominal Input Sensitivity (Unbal. Line): -12 dBV (250 mVrms)
THD+N (Pre-Out, @ -6dB): < 0.1%
Frequency Response (-3dB): 20 Hz – 20 kHz
Input Impedance: 10 kW
OUTPUTS
Number of Output Channels: 1
Output Connectors: 4-pin, 0.3 inch (7.6 mm) Euroblock
70V/100V Mode: Yes
Low Impedance Mode: Yes
Priority Output Contact: Yes
Minimum Operational Load: 4W
Amplifier
Topology: Class D
RMS Output Power (1% THD): 30 W
Dynamic Power: 35 W
SNR (1% THD): > 90 dB
THD+N (@ -6dB): < 0.5%
Protection: Temperature, overcurrent, overvoltage, undervoltage
Priority Output
Voltage: 24V
Max Current: 0.5A
Pre-Out
Nominal Output Level: 0 dBV
Standby
Wakeup Sensitivity:
Inputs 1-2: -44 dBV (6 mVrms ± 10%)
Mic (RCA): -46 dBV (5 mVrms ± 10%)
Mic (Balanced, VOX off): -70 dBV (0.3 mVrms ± 10%)
Time to Auto Standby: 10 min
Power Consumption (100-240VAC 50/60Hz)
Normal Operation: 60W
Idle Operation: 4.5W
Standby Mode: 0.5W
Fuse: 1AL
Cooling: Convection
Overall Dimensions
Height (without feet): 3.5 inches (89 mm)
Width: 8.5 inches (216 mm)
Depth: 9.8 inches (250 mm)
Weight: 5.3 lbs (2.4 kg)
Environmental Ambient Operating
Temperature Range: 32 - 95° F (0 – 35° C)
Humidity: 0-95% relative humidity (non-condensing)

Altitude: 0-6,600 ft (0-2000m) MSL
Compliance
FCC Part 15B (USA)
UL listed (USA and Canada) CE Marked (Europe) RoHS Directive (Europe)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.