

ELECTROCOMPANIET Nemo (AW600) Mono Block

Šifra: 13178
Kategorija proizvoda: Pojačala Snage
Proizvođač: Electrocompaniet

Cena: **1.115.880,00** rsd

The stunning capabilities of the Electrocompaniet AW600 can not be explained - they have to be experienced.

The AW600 incorporates such refined features as: FTT (Floating Transformer Technology) power supply, capable of delivering twice the current of a conventional power supply, a first class overall circuit design and state-of-the-art components

Power and control, but with a liquid, spaciuous and effortless approach that removes any hint of electronic interference, leaving only Sheer, clear music in their wake. Extreme Sonic value for money, they set a new standard for power amplification.

Audio & Video South Africa

"Absolut Spitzenklasse, Überagend-58 punkte."

(59 points is the highest score on a power amp as tested in Stereoplay, and it costs 2-3 times more)
Stereoplay Germany

"A Manly Man Of An Amplifier"

- Up with the best valvejobs I've ever heard and grainless liquidity that no other solid-state amplifier I've heard can match.

A cross between Singel ended triode and Arnold Schwarzenegger. Unlimited power and bottom slam, handles complexity without a hint of confusion. Enormously wide and deep Soundstage. I would pick them up every other solid-state amplifier I've heard.

Ultimate Audio, Winter 2000

All measurements are made at 120V / 240V //50Hz / 60Hz

Amplifier section

Clipping point of the preamplifier is set to a level where total harmonic distortion (THD) is 0.2%

Input Impedance (Fixed)	330 kohm
Output Impedance (20 Hz-20kHz)	< 0,009 Ohm
Frequency response (DC - 65 kHz)	- 0.4 dB
Input level for rated output	1 V RMS
Max. peak current	> 150 A
THD(measured at 1 kHzhalf power,8W)	< 0,001 %
THD (measured at 1 kHz -1 dB, 8 W)	< 0,0015 %
Noise	400 Hz - 30 kHz : 150 µV
(measured with bothinputsshorted)	DC - 30 kHz : 200 µV
Damping factor (20 Hz - 20 kHz)	> 850

Rated output power

8 ohms	600 W
4 ohms	1200 W

Power consumption (no load or signal) 230 W

The NEMO is DC coupled from input to output

Dimensions

Width	465 mm / 18.3 inches
Depth	450 mm / 17.7 inches
Height	288 mm / 11.3 inches
Weight	41 kg. / 90.2 lbs.