

ARX Network DI

Šifra:
Kategorija proizvoda: DI Box i Phantom Power
Proizvođač: ARX

Cena: **59.880,00** rsd

The **Network DI** is designed to receive audio channels from a **Dante** network and provide studio quality, low latency audio via balanced XLR output connectors to analog audio equipment.

Thus any audio available on the network can be converted to Analog and routed via the **Network DI** to, for example, an amplifier, or powered speaker(s), mixing console, digital signal processor and many other analog audio devices.

Dante Audio In

Input Connector 1 x RJ45 Ethernet

Sample Rate 44.1KHz, 48 KHz (default), 96KHz

Bit Depth 24 Bits

Network Speed 100 Mbps

Power Consumption 2 Watts max.

Power over Ethernet Class 1 802.3af POE PD compliant

Analog audio out

Output Connectors 2 x Male XLR connectors, Pin 1 Chassis ground, Pin 2+, Pin 3-

Output impedance 150 ohm balanced, 75 ohm unbalanced

Output Level +4dBu @ 0dBFS

Frequency Response 20Hz - 20 kHz +/- .5dB

Dynamic range < 100dB

Signal to noise < 100dB

THD <.01% at +4dBu

Features: Mono Switch L & R summation

Construction: All-steel chassis, fibreglass PCB, epoxy printing, slip-resistant rubber base pad

Precision engineered

With a couple of exceptions, all products in the Audibox range share a common footprint and manufacturing platform. Offset lid screws enable close side-by-side mounting of multiple units.