

## ARX DI-PLUS RC

Šifra: 00000

Kategorija proizvoda: DI Box i Phantom Power

Proizvođač: ARX



**Cena: 25.080,00 rsd**

The **DI Plus RC** will automatically switch itself to the console's own Phantom Power, if available, and an LED will indicate this mode. Turn the Phantom Power off and it will instantly revert back to battery mode.

### Rugged all-steel case

A lot of direct boxes are fitted into brittle cast alloy cases. Not this one! The tough all-steel inner and outer chassis of the **DI Plus RC** provide excellent RF/EMF shielding while making it a sturdy, heavy duty unit that is hard to dislodge, and hard to leave behind.

### Max Input Level

+13 dB Phantom powered  
+6 dB Battery powered

### Input Impedance 1 Meg Ohm

### Max Output Level

+17 dB 10K Ohm load Phantom powered  
+12 dB 10K Ohm load Battery powered  
+11 dB 600 Ohm load Phantom powered  
+12 dB 600 Ohm load Battery powered

### Output Impedance 680 Ohms Balanced

### Output Signal to Noise

-100 dB unweighted  
-104 dB A weighted

### Dynamic Range

117 dB 10K Ohm load Phantom powered  
112 dB 10K Ohm load Battery powered  
111 dB 600 Ohm load Phantom powered  
107.5 dB 600 Ohm load Battery powered

### Distortion

100 Hz .0027%, 1KHz .0028%, 10KHz .0037%

### Frequency Response 20Hz to 20KHz, $\pm 0.2$ dB

### Gain through Unit: 6dB (Normal input, Pad switch out)

### Pad Switch: -20 dB attenuation

### Speaker Input

-40 dB attenuation, equivalent to 100:1 decrease in input level  
-60 dB attenuation available with Pad switch

### Input Connectors

Insulated jacks (!!!Note that the Input connectors switch the unit on when a plug is inserted. Remove plug when storing to avoid battery drain!!!)

**Output Connector**

3 pin XLR. Wired Pin 1 Ground, Pin 2 + Hot, Pin 3 - Cold.  
With Audio Ground (Pin 1) lift switch

**Construction**

All-steel chassis, fibreglass PCB, NiMH battery