

FBT JMAXX 114A - Aktivni zvučnik

Šifra: 14368

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: FBT

Cena: 76.680,00 rsd



Processed 2-way active loudspeaker
700W + 200W - 132 dB SPL (peak)

The new FBT JMaxX 114A combines ease of use and versatility for many portable or installed sound applications: musicians, DJs, AVL contractors, rental sound reinforcement, corporate events, houses of worship, bars and clubs.

With its eye-catching gas-injected forms designed to virtually eliminate undesired enclosure resonance and reinforce strong low frequency performance, the 14-inch JMaxX 114A is equipped with FBT's latest 90° x 60° HF horn design which delivers improved projection, accuracy, and dispersion of the mid and high frequencies.

Providing a myriad of possibilities for bands, DJs and solo artists, as well as for permanent installations, the JMaxX 114A is actually four loudspeakers in one. Derived from a decade of experience of portable sound reinforcement, the carefully tailored equalisation presets offer highly intelligible response for vocals and floor monitoring; slightly boosted response in lounge bar applications; punchy and forward sound for DJs and night venues; and a general-purpose EQ setting that mirrors the original and familiar FBTMaxX voicing.

The JMaxX 114 A features FBT's latest generation lightweight 700W + 200W Class D power amplifier with universal switch mode power supply, delivering abundant power and headroom to reproduce even the largest transients without distortion.

And a unique 14 Inch Low frequency driver. The 14" Driver fits inside a cabinet the size of a 12" Cabinet yet performs as good as a conventional 15".

This unique speaker.

The result is an amazingly compact speaker with all the power and clarity of a much larger speaker and weighing just 14Kg this Speaker is a dream to transport.

XLR inputs and outputs, volume control, the EQ presets and filters, and ground lift switch are all conveniently located on a clearly laid out rear panel, making loudspeaker setup and operation intuitive and consistently repeatable.

The JMaxX versatility is further underscored by the many mounting and fixing options that the ergonomically styled cabinets provide. Mounting in fixed installations is made easy using the M10 suspension points or wall bracket flange plates, while portable use is facilitated by the built-in 35mm pole mount socket.

There's no need for separate stage monitors, as JMaxX's cabinet profiles are designed with 14°, 40°, and 55° wedge angles, and when used with the specific floor monitoring EQ presets, will ensure that performers hear themselves with ultimate clarity.

Weighing just 14Kg and Packing a genuine 900 Watts RMS The JMaxX 114A is setting a new standard in compact affordable lightweight speakers.

KEY FEATURES

Configuration: 2 way

Built-in amplifier LF/HF: 700/200 W RMS

Built-in amplifier peak LF/HF: 1400/400 W

Frequency response: 45Hz - 20KHz -6dB

Low Frequency woofer: 14 - 2.5 coil inch

High Frequency driver: 1 - 1.4 coil inch

Maximum SPL cont/peak: 126 / 132 dB

Dispersion: 90° x 60° HxV

Input impedance: 22 K

Crossover Frequency: 1.6 KHz

AC Power requirements: 640 VA

Input connector: XLR with loop, Jack 6.3mm

Power cord: 5 16,4 m/ft

Net Dimension (WxHxD): 402x644x345 15,8x25,4x13,6 mm/inch

Net Weight: 14 Kg/lb

Transport Dimension (WxHxD): 500x745x440 19,7x29,3x17,3 mm/inch

Transport Weight: 16.6 36.6 Kg/lb

Configuration:

2 Way

Frequency response:

45Hz - 20kHz

Low frequency woofer:

14" (2.5" VC)

High frequency driver:

1" (1.4" VC)

Maximum SPL cont/peak:

132 dB

Dispersion:

90 x 60

Input connector:

XLR + 6.3mm Jack

Net Weight:

14kg

Built-in amplifier LF/HF:

700w/200w

Power cord:

5m IEC