

Mogami 2319 - Instrumentalni kabl - Gitarski

Šifra: 14389
 Kategorija proizvoda: Na Metar Instrumentalni
 Proizvođač: Mogami



Cena: 300,00 rsd

SPECIFICATIONS

Configuration		mogami guitar cable w2319d		mogami guitar cable w2524d	
Part No.		W2319		W2524	
Conductor	Details	12/0.18TA		50/0.12A	
Size(mm ²)		0.305mm ² (#23AWG)		0.565mm ² (#20AWG)	
Insulation	Ov. Dia.(mm)	1.6Ø (0.063")		2.7Ø (0.106")	
	Material	PE			
Color	Clear				
Sub-Shield	Ov. Dia.(mm)	1.8Ø (0.071")		3.3Ø (0.130")	
	Material	Conductive PVC (Carbon PVC)			
Color	Black				
Main-Shield	Served-Shield	Approx. 38/0.16TA		Approx. 55/0.18A	

Jacket	Ov. Dia.(mm)	5.0Ø (0.197")	6.0Ø (0.236")
Material	PVC		
Color	Black		
Roll Sizes	100m (328Ft)	100m (328Ft) / 200m (656Ft)	
Weight per 100m (328Ft) roll	3.5Kg	5.1Kg	

ELECTRICAL & MECHANICAL CHARACTERISTICS

Part No.	W2319	W2524
DC Resistance at 20°C	Inner Conductor 0.064Ω/m(0.020W/Ft)	0.033Ω/m(0.010Ω/Ft)
Shield Conductor	0.026Ω/m(0.0079Ω/Ft)	0.014Ω/m(0.0043Ω/Ft)
Capacitance at 1kHz, 20°C	155pF/m (47.3pF/Ft)	130pF/m (39.7pF/Ft)
Inductance	0.3μH/m (0.092μH/Ft)	0.2μH/m (0.061μH/Ft)
Electrostatic Noise*	0.13mV Max.	0.15mV Max.
Electromagnetic Noise At 10kHz*	0.07mV Max.	0.07mV Max.
Microphonics*	0.3mV Max	0.3mV Max
Voltage Breakdown	Must withstand at DC 500V/15sec.	
Insulation Resistance	100000 MΩ × m Min. at DC 500V , 20°C	

Flex Life	11,000 cycles	15,000 cycles
Tensile Strength (26°C, 65%RH)	303 N	578 N
Emigration	Non-emigrant to ABS resin	
Applicable Temperature	-20°C - +60°C (-4°F - +140°F)	