

# Mogami 2319 - Instrumentalni kabl - Gitarski

## Mogami 2319 - Instrumentalni kabl - Gitarski SPECIFICATIONS

Šifra: 14389

Kategorija proizvoda: Na Metar Instrumentalni kabl - gitarski

Proizvođač: Mogami

Part No.

W2319

W2524

**Cena: 300,00 rsd**

		mogami guitar cable w2319d	mogami guitar cable w2524d
Conductor	Details	12/0.18TA	50/0.12A
Size(mm <sup>2</sup> )		0.305mm <sup>2</sup> (#23AWG)	0.565mm <sup>2</sup> (#20AWG)
Insulation	Ov. Dia.(mm)	1.6Ø (0.063")	2.7Ø (0.106")
	Material	PE	
Color		Clear	
Sub-Shield	Ov. Dia.(mm)	1.8Ø (0.071")	3.3Ø (0.130")
	Material	Conductive PVC (Carbon PVC)	
Color		Black	
Main-Shield	Served-Shield	Approx. 38/0.16TA	Approx. 55/0.18A
Jacket	Ov. Dia.(mm)	5.0Ø (0.197")	6.0Ø (0.236")
	Material	PVC	
Color		Black	
Roll Sizes		100m (328Ft)	100m (328Ft) / 200m (656Ft)
Weight per 100m (328Ft) roll		3.5Kg	5.1Kg

## ELECTRICAL & MECHANICAL CHARACTERISTICS

Part No.	W2319	W2524	
DC Resistance at 20°C	Inner Conductor	0.064Ω/m(0.020W/Ft)	0.033Ω/m(0.010Ω/Ft)
Shield Conductor	0.026Ω/m(0.0079Ω/Ft)	0.014Ω/m(0.0043Ω/Ft)	
Capacitance at 1kHz, 20°C	155pF/m (47.3pF/Ft)	130pF/m (39.7pF/Ft)	
Inductance	0.3μH/m (0.092μH/Ft)	0.2μH/m (0.061μH/Ft)	
Electrostatic Noize*	0.13mV Max.	0.15mV Max.	
Electromagnetic Noise At 10kHz*	0.07mV Max.	0.07mV Max.	
Microphonics*	0.3mV Max	0.3mV Max	
Voltage Breakdown	Must withstand at DC 500V/15sec.		
Insulation Resistance	100000 MΩ × m Min. at DC 500V , 20°C		
Flex Life	11,000 cycles	15,000 cycles	
Tensile Strength (26°C, 65%RH)	303 N	578 N	
Emigration	Non-emigrant to ABS resin		
Applicable Temperature	-20°C - +60°C(-4°F - +140°F)		

