Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Mogami 2552 - Mikrofonski kabl

Šifra: 14386
Kategorija prozivoda: Na Metar Mikrofonski
Proizvođač: Mogami



Cena: 300,00 rsd

Part No. W2552 & W2582

Mogami Cable Part No. W2582

Superflexible Light Weight Mic. Cables With Overall Shield

Here is an extremely limp and flexible cable for all types of audio/visual and industrial audio applications. XLPE insulation and a strong rubber - like outer jacket makes this cable ideal where a durable yet economical cable is needed.

Part No.	W2552	W2582
O.D. (mm)	5.0ø (0.197")	6.0ø (0.236")
Flex Life	11,000 cycles	13,800 cycles
Tensile Strength	421 N	441 N
Colors	Black	Black / Red / Yellow / Green / Blue / Gray

Part No. W2447 & W2435

Mogami Cable Part No. W2447

Superflexible Light Weight Mic. Cables With Individual Shield

A durable and mechanically strong cable similar to W2552 but with two separately served shields. This produces capacitance level a little higher than that of W2552.

Part No.	W2447	W2435
O.D. (mm)	5.0ø (0.197")	6.0ø (0.236")
Flex Life	14,000 cycles	24,000 cycles
Tensile Strength	451 N	451 N
Colors	Black	Black

Part No. W2792

Mogami Cable Part No. W2792

Image not found or type unknown

Low MicrophonicS Mic. Cable With Conductive PVC

Conductive material is coated on top of the XLPE insulation which reduces microphonic handling noise to negligible level even in high impedance applications. Before soldering the black coating shall be stripped back.

Part No.	W2792
O.D. (mm)	6.0ø (0.236")
Flex Life	22,000 cycles
Tensile Strength	490 N
Colors	Black / Red / Yellow / Green / Blue / Gray

SPECIFICATIONS

Configuration	mogami cable diagram w2552 Image not found or type unknown	mogami cable diagram w2447 Image not found or type unknown	mogami cable diagram Image not found or type unknown

Part No.		W2552	W2582	W2447	W2435	W27
No. of Conductor		2				
Conductor	Details	12/0.12 A <T250D*3>				
Size(mm²)		0.135mm² (#26 AWG)				
Insulation	Ov. Dia.(mm)	1.5Ø (0.059")				
	Material	LNXLPE (Low Noise Cross-Linked Polyethylene)				
Colors		Red / Clear				
Served Shield		Approx. 67/0.12A	Approx. 36/0.12A	Approx. 95/0.12A		
Jacket	Ov. Dia.(mm)	5.0Ø (0.197")	6.0ì (0.236")	5.0Ø (0.197")	6.0ì (0.236")	
	Material	Flexible PVC				
Colors		Black	Black / Red / Yellow / Green / Blue / Gray	Black	Black	Black / Red / Yellow / Green / Blue / Gray
Roll Sizes		50m (164 Ft) 100m (328Ft) 200m (656Ft)	50m (164 Ft) 100m (328Ft) 200m (656Ft)	100m (328Ft) 200m (656Ft)	100m (328Ft) 200m (656Ft)	50m (164 Ft) 100m (328 200m (656
Weight per 200m Roll		7.5kg	9kg	7.7kg	9kg	8.8k

ELECTRICAL & MECHANICAL CHARACTERISTICS

Part No.		W2552	W2582	W2447	W2435	W2792
DC Resistance at 20°C	Inner Cond.	0.14W/m(0.043W/Ft)				

Shield	0.024Ω/m(0.007Ω/Ft)		0.021Ω/m(0.006Ω/Ft)		0.018Ω/m(0.005Ω/Ft)							
Capacitance at 1kHz, 20°C (Partial C. Value) See below figure*	K_0	90pF/m(27pF/Ft)		123pF/m(37.5pF/Ft)				127pF/m(38.7pF/Ft)				
K_1	10pF/m(3pF/Ft)	-										
Inductance between conductors at 1kHz. 20°C	0.8µH/m(0.24µH/Ft)											
Electrostatic Noise**	50mV Max.		50mV Max.				0.5mV Max.					
Electromagnetic Noise**	0.15mV Max.											
Microphonics at 50KW Load**	30mV Max.	30mV Max.	30mV Max.				30mV Max.				1mV Max.	
Voltage Breakdown	Must withstand at DC 500V/15sec.											
Insulation Resistance	100000 MW × m Min. at DC 125V, 20°C											
Flex Life**	11,000 cycles	13,800 cycles	14,000 cycles				24,000 cycles				22,000 cycles	
Tensile Strength	421N	441N	451N				480N				490N	
Emigration	Non-emigrant to ABS											
Applicable Temperature	-20°C¯ +70°C(-4°F¯ +158°F)											

** Using standard testing methods of Mogami Wire & Cable Corp.	* Partial Capacitance
Partial Capacitance w2552 Image not found or type unknown **W2552/W2582**	Partial Capacitance w2447 Image not found or type unknown **W2447/W2435/W2792**

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.