

MARTIN AUDIO SX118 - Pasivni vufer

Šifra: 14937

Kategorija prozivoda: Pasivni Subwooferi

Proizvođač: Martin Audio

Cena: 251.880,00 rsd

MARTIN AUDIO SX118 - Pasivni vufer

Features

Compact, direct radiating subwoofer
18" (460mm)/4" (100mm) voice coil, long excursion,
ferrite magnet, waterproof cone
High output capability
Tour-grade plywood enclosure with flying inserts

Applications

Touring sound reinforcement for small and medium-

size venues

Fixed installations in concert halls, theatres, ballrooms and HoW

Sports stadium, arena installations & corporate AV events

Outdoor restaurant, bar and hotel entertainment areas

Concourses and Theme Parks

SX118 features a long-excursion 18" (460mm)/4" (100 mm) voice coil driver with a water-resistant cone and triple roll surround in a compact reflex enclosure.

The design of the 18" driver maximises output while minimising power compression and distortion, and the four reflex ports have a large frontal area to reduce turbulent air noise at very high levels. The enclosure is constructed from multi-laminate birch ply, finished with a durable polyurea coating and equipped with a Zintec grille, twin grab handles, skids, flying inserts for installation and a threaded pole socket for pole-mounting point source loudspeakers or up to 4 WPM enclosures as a simple plug-and-play system.

The product is supplied as standard without cabinet wheels, but they are available as an accessory.

By adding the input board cover accessory, SX118 is fully weather resistant and suitable for permanent outdoor usage.

TYPE Compact, direct radiating subwoofer

FREQUENCY RESPONSE (1) 47Hz - 150Hz ±3dB,

-10dB @ 41Hz

DRIVER 18" (460mm)/4" (100mm) voice coil, long excursion, ferrite magnet, waterproof cone

RATED POWER (2) 1000W AES, 4000W peak

SENSITIVITY (10) 102dB

MAXIMUM SPL (9) 138dB peak

NOMINAL IMPEDANCE 8Ω

DISPERSION (-6DB) Omnidirectional/or Cardioid (paired)

ENCLOSURE Multi-laminate birch/poplar ply

FINISH Durable Polyurea Coating

PROTECTIVE GRILLE Black perforated Zintec

CONNECTORS 2 x NL4 type

PIN CONNECTIONS (INPUT) LF: +1, -1 Link through: +2, -2

PINS CONNECTIONS (LINK) LF: +1, -1 Link through: +2, -2

FITTINGS

Two skids on base, with mating channels on top

M20 top-mounted thread plate for pole mounting

16 x M10 mounting points

2 x bar handles, 1 on each side

4 x fittings for optional transit cover

16 x M8 inserts for optional castors

DIMENSIONS (INCL SKIDS)

(W) 600mm x (H) 509mm x (D) 632mm

(760mm including castors)

(W) 24in x (H) 20.36in x (D) 25.26in

(30.38in including castors)

WEIGHT 43.5kg (96lbs) w/o castors 47kg (104lbs) with castors