logo
Image not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

BEYERDYNAMIC TG550 Vocal Dynamic
Image not found or type unknown

BEYERDYNAMIC TG550 Vocal Dynamic

Šifra: 15175
Kategorija prozivoda: Wireless Mikrofoni
Proizvođač: Beyerdynamic

Cena: 69.480,00 rsd

WHAT'S IN THE BOX:

- TG 500SR (single receiver)
- TG 500 H-D (handheld transmitter with dynamic TG V50 capsule)
- Microphone clamp
- 1 pair of detachable antennas
- Batteries
- Power supply
- Rack mount kit

TG 500SR
The heart of each beyerdynamic TG 500 wireless system is an attractively designed receiver with a robust metal housing. Intuitively operating elements in combination with a backlit LC display enable a particularly user-friendly menu navigation. The frequency response of the system is from 45 to 15 kHz. A balanced XLR output and a balanced jack output are provided as analogue audio ports.

RACK MOUNT KIT
When mounting the single receiver into a 19" rack it requires 1 U. The supplied rack mount kit allows two 9.5" devices to be installed in one rack.

FEATURES
• Intuitive, user-friendly menu structure
• Up to 40 MHz switching bandwidth
• Infrared interface for transmitting settings from the receiver to the transmitter
• Backlit LC display
• Status display (battery, frequency, name)
• Scan function
• BNC antenna outputs
• XLR and jack output (balanced)
• Detachable BNC antennas
• Pilot tone function

TECHNICAL SPECIFICATIONS
System
Frequency range. . . . . 518 – 548 MHz
606 – 636 MHz
794 – 832 MHz
925 – 937.5 MHz*
1,785 – 1,805 MHz

Transmission range . . . . . up to 120 m
(line of sight)
Number of the simultaneously
active channels . . . . . 18 per frequency band
Audio frequency response . . . . . 45 – 15 kHz
Audio dynamic range . . . . . 106 dB (A-weighted)
Operating principle. . . . . Analogue wireless
microphone system
with diversity receiver
Single receiver
Output level . . . . . max. +3 dBV / +5 dBu
Display . . . . . 2 x LCD, white backlit
Mains connection . . . . . 100 – 240 V AC with
power adapter
Power consumption . . . . . 3 W (typ.)
Ambient temperature . . . . . 0 to +55 °C
Weight . . . . . 960 g
Dimensions. . . . . 200 x 175 x 42 mm
Antenna connection . . . . . 2 x BNC input

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.