

Pioneer XPRS10 - Aktivni zvučnik

Šifra: 15185

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: Pioneer DJ

Cena: 143.880,00 rsd



The XPRS10 single PA speaker combines a 10-inch ferrite LF driver, a 1.75-inch titanium diaphragm compression driver and Pioneer Pro Audio's AFAST technology to deliver crystal clear audio with a deep bass range. Being compact, plug-and-play and easy to transport, this speaker is a reliable partner on the road, for any venue.

Natural, full-range sound

The 15-mm birch plywood cabinet, 10-inch ferrite LF driver and 1.75-inch titanium diaphragm compression driver reproduce a clean, full-range sound with low distortion, even at high outputs. Plus, the XPRS10's compact horn sounds bright and clear.

Powersoft Class D amps

Powersoft's Class D amp modules produce 2400 W (peak) or 1200 W (continuous) output. The Power Factor Correction (PFC) reduces power consumption while ensuring steady performance in all environments.

AFAST acoustic tube

Pioneer Pro Audio's AFAST technology drastically reduces standing waves that can produce a muffled response in the low to mid ranges. An acoustic tube in the cabinet absorbs only the standing waves, increasing the low-to-mid frequency response.

4 EQ modes

Adapt to a variety of genres and environments using the rotary selector switch on the back of the speaker to give you instant access to 4 EQ modes: Flat, Bass +, Speech and Wedge.

Advanced protection

The XPRS speaker is packed with features to protect the drivers, amp and power supply in to Amplifier module - giving you peace of mind, consistent high-quality sound, and extending the life of your sound system.

Flexible connectivity

2 balanced XLR/TRS combo sockets and an unbalanced RCA connection mean you can connect at the same time a Mic and other devices, such as line-level mixers or portable audio players.

Designed for the road

The durable, birch plywood enclosure keeps your PA speaker safe, while carefully placed handles take the hard work out of transit and set-up.

Auto-ranging power supply

Plug in the XPRS Series anywhere in the world - including venues with generators or temporary power supplies. They will detect and adapt to the voltage without compromising the sound quality.

Specifications

Main Features

What's in the box	XPRS 10 x 1 Powerd cord Installation and Operation Manual Important Safety Precautions
--------------------------	---

Specifications

Width	320 mm
Height	520 mm
Depth	374 mm

Weight	18.9 kg
---------------	---------

Frequency Range	55 - 20000 Hz
------------------------	---------------

System characteristic

Maximum Sound Pressure	134 dB
-------------------------------	--------

Cross Over Frequency	2 kHz
-----------------------------	-------

Terminals

Inputs	2 XLR/TRS Combo (balanced) 2 RCA (unbalanced)
---------------	--

Outputs	2 Through output XLR (balanced) 1x Mixed output XLR (balanced)
----------------	---

Amplifier

Amplifier Output	Class D 2400W peak / 1200W cont. (LF800W / HF400W)
Impedance	10 kΩ

Speaker

Driver	10 inch ferrite LF cone driver 1.75 inch titanium diaphragm neodymium compression driver
Enclosure	15 mm birch plywood