Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Pioneer XPRS-215S - Aktivni vufer



Šifra: 15189
Kategorija prozivoda: Aktivni Subwooferi
Proizvođač: Pioneer DJ

Cena: 149.880,00 rsd

Enhance your lower frequencies with the quick and powerful bass response of the XPRS215S subwoofer. The sub’s built-in horn shape and dual 15-inch, high-grade ferrite LF drivers deliver rich, powerful low frequencies, while the Crossover and Phase switches allow you to control your DSP settings effortlessly.

* The XPRS215S is sold as a single subwoofer.

Double the bass

The XPRS215S’ birch hardwood cabinet encloses two 15-inch LF drivers and a built-in horn shape to deliver rich, powerful low frequencies, no matter the event or the setting.

Powersoft Class D amps

Powersoft’s Class D amp modules produce 2400 W (peak) or 1200 W (continuous) output. The Power Factor Correction (PFC) reduces power consumption while ensuring steady performance in all environments.

Instant control

A versatile Crossover switch lets you adjust the low pass filter cut-off at stages between 80 Hz and 150 Hz. At the same time, the Phase switch allows you to choose a positive or negative polarity to prevent multiple subwoofers from cancelling each other out.

Advanced protection

The XPRS subwoofer is packed with features to protect the drivers, amp and power supply – giving you peace of mind, consistent high-quality sound, and extending the life of your sound system.

Flexible connectivity

The subwoofer has 2 balanced XLR/TRS combo sockets so you can input a couple of devices at the same time. Plus 2 balanced XLR through outputs enable easy connection to other speakers and subs.

Designed for the road

The durable, birch plywood enclosure keeps your subwoofer safe, while castors on the back of sub and carefully placed handles take the hard work out of transit and set up.

Auto-ranging power supply

Plug in the XPRS Series anywhere in the world – including venues with generators or temporary power supplies. They will detect and adapt to the voltage without compromising the sound quality.

Up to a 7-year warranty

We're extending the free warranty period for the XPRS Series active speakers. You can now receive up to 7 years of cover by registering your products online within 90 days of your purchase. Please review the warranty statement for a full list of terms and conditions.

Specifications

Main Features

What's in the Box	XPRS 215S x 1 Powerd cord Installation and Operation Manual Important Safety Precautions

Specifications

Supported voltages	100 V (50 Hz/60 Hz) 110 V to 240 V (50 Hz/60 Hz)
Width	743 mm
Height	524 mm

Depth	811 mm
Weight	55.9 kg
Frequency Range	40 - 160 Hz

System characteristic

Maximum Sound Pressure	135 dB

Terminals

Inputs	2 XLR/TRS Combo (balanced)
Outputs	2 Through output XLR (balanced)

Amplifier

Amplifier Output	2400W peak / 1200W cont. Class D
Impedance	10 kΩ

Speaker

Driver	15 inch ferrite LF cone driver
Finish	Impact-resistant Black semi-matt textured
Handle	4 (on both sides)
Pole socket	M20 screw socket
Enclosure	15 mm birch plywood

Protection

Amplifier Protection	Thermal limiting Over-temperature muting Output overcurrent
Driver Protection	DC offset removal High frequency stationary loud signals Input voltage limiter (Peak/RMS)
Power unit Protection	Primary AC mains overcurrent protection Primary AC mains overvoltage protection

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.