

QED SAXT SPEAKER CABLE 3M

Šifra: 15411

Kategorija proizvoda: Hi-Fi Analogni kablovi

Proizvođač: QED

Cena: 16.680,00 rsd

X-TUBE with Aircore technology exhibits much lower self-inductance. The use of an innovative Polyethylene aircore enables a reduction in loop inductance to levels only usually achievable by using more costly and difficult to terminate cables.

Silver plated 99.99% OFC Conductors

Compressible Teflon Aircore for ease of termination

Low resistance, low capacitance and low inductance

Easy strip Polyethylene outer jacket

Cross-sectional area 1.50mm²

X-Tube Technology How It Works

X-Tube Technology - How It Works

One of the big problems as cable conductor size increases, is how to keep the inductance low. This is vital to reduce cable losses and prevent inaccuracies in the

QED SAXT SPEAKER CABLE 3M

Silver

Anniversary-XT has been specifically designed as the natural replacement for the multi-award winning QED Silver Anniversary speaker cable.

Designed with performance in mind, the Silver Anniversary-XT speaker cable boasts all of the characteristics associated with Silver Anniversary but with the added enhancement of the Aircore technology found in the prestigious X-Tube series.

signal transfer process, (i.e. distortion). The normal way to do this is to use a number of individually insulated conductors within the cable construction. This method is utilised to great effect in the design of our Genesis Silver Spiral loudspeaker cables. However, this results in a product that has a very high quality sound performance, but is expensive to manufacture and can be difficult to terminate. To take advantage of this design ethos, but in a more conventional

format,
X-TUBE
forms
the
conductor
in the
shape of
a tube
with an
inner
Aircore.
This has
the
same
effect as
using
multiple
insulated
conductors
and
ensures
that high
frequencies
are
transmitted
cleanly,
with the
added
benefit
of ease
of
termination.
This
unique
tubular
conductor
geometry
also
provides
lower
flux
density
within
the
conductors,
which
gives
improved
transparency
to the
sound.

X-Tube - The Signal
Image not found or type unknown

X-Tube - The Signal

At low
frequencies
both X-
TUBE
and
conventional
stranded/solid
core
speaker
cable
convey
signals
in a
linear
way.
This is
represented
by the
uniform
green
colour of
the
strands
shown in
the two
diagrams
above.
At
higher
frequencies
X-TUBE
retains a
near-
linear
signal
transfer,
whereas
the
conventional
stranded/solid
core
cable
fails to
efficiently
conduct
higher
frequencies
uniformly
across
the
entire
conductor

area.
The diagram shows excess current density at the periphery (designated in red) and rapidly deteriorating current density (green through to white) towards the centre of the conductor. The effect of this is to reduce the actual cross-sectional area of the cable at 15kHz to less than 75% of that at low frequencies. The result is induced distortion and a compromise in the performance of the cable.

Wire gauge	16 AWG
------------	--------

Unique SPOFC triple braid	5 x 16 x 0.1mm
----------------------------------	----------------

Jacket OD	3.90mm
------------------	--------

Cross-sectional area	1.50mm ²
-----------------------------	---------------------

Loop resistance	0.021 Ω /m
------------------------	-------------------

Inductance	0.47 μ H/m
-------------------	----------------

Dissipation factor	0.0006
---------------------------	--------