Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Biamp Devio SCR-25TX Black - Konferencijski audio kontroler



Šifra: 15434
Kategorija prozivoda: Konferencijski / Instalacijski Mikrofoni
Proizvođač: Biamp

Cena: 395.760,00 rsd

Product Features
Devio SCR-25
Works in concert with PCs running web-based conferencing solutions, including Microsoft Skype for Business/Microsoft Teams, Zoom, BlueJeans, Google Hangouts™/Google Meet, and many more
Supports both Windows and Mac PCs, and uses standard audio drivers
Supports driverless, pass-through HDMI connectivity to a single in-room display, or to two monitors with USB video using DisplayLink USB graphics technology (requires installation of DisplayLink driver on laptop; supports Windows 7, 8, 8.1, and 10)
Auto Setup validates device connections, adjusts room levels, and sets speaker EQ to optimise audio quality
Supports Bluetooth wireless technology
Can be monitored and managed remotely via SNMP or with the Devio System Administration Utility (SAU)
Firmware updates can be scheduled and deployed to multiple Devio units via the SAU
Speaker connectivity options include HDMI audio, a built-in 20W amplifier, or RCA line out
Includes a mounting bracket for under–the–table installation
Ships with and one tabletop or ceiling Beamtracking microphone with 360-degree coverage
Covered by Biamp Systems' two-year warranty
Parlé TTM-XEX Tabletop (Black)
Measures 4.7 inches (120 mm) in diameter
Sits directly on a tabletop to virtually disappear in room
Beamtracking technology actively tracks and intelligently mixes conversations
Four 90-degree zones for full 360-degree room coverage
Uses only one channel of AEC per mic
Single cable connection via category cable
Beamtracking technology works out-of-box without any lobe aiming or room mapping
LED mute status indicator
Available in either black or white
CE marked, UL listed, and RoHS compliant
Covered by Biamp Systems' two-year warranty
Product Specifications
Devio SCR-25
Network Connection: RJ-45 with Ethernet cable (Cat 5e and above)
Front Panel Indicators:
Mic Status Indicator (Green/Red LED)
Room Tuning Indicator (Green/Red LED)

Power/Wireless Indicator (Green/Red/Blue LED)
Power: 24V DC 60W
Video
Supported Resolutions:
640 x 480p (60 Hz)
720 x 480p (60 Hz)
720 x 576p (50 Hz)
1280 x 720p (50/60 Hz)
1920 x 1080p (50/60 Hz)
3840 x 2160p (30 Hz)
Physical Interface: HDMI
HDCP Support: 1.4
HDMI Audio Formats: 2ch L-PCM, 44.1 kHz/48 kHz, 16-bit
Headset
Frequency Response (200 Hz - 8 kHz, FS): ±0.5 dB
THD+N (1 kHz - 4 kHz, 8 kHz B/W, FS): < 0.05%
Dynamic Range (THD+N < 0.05%): 80 dB, A-Weighted
Maximum Output: -3 dBu
Analogue Audio Output (RCA)
Frequency Response (20 Hz - 20 kHz, FS): +0/-0.25 dB
THD+N (20 Hz - 10 kHz, 20 kHz B/W, FS): < 0.005%
Dynamic Range (THD+N < 0.005%): 107 dB, A-Weighted
Output Impedance (unbalanced): 100Ω
Maximum Output: +8.5 dBu
Sampling Rate: 48 kHz
D/A Converters: 24-bit
Amplifier
Number of Channels: 1
Continuous Power Output
(THD+N < 0.025%): 20 W into Rated
Load Impedance
Frequency Response
(20 Hz - 20 kHz): +0.2/-0.5 dB
THD+N (1 kHz, 20 kHz bandwidth, 1 W): < 0.03%
Dynamic Range (THD+N < 0.5%): 100 dB, A-Weighted
Minimum Operational Load: 4Ω
Intermodulation distortion
(SMPTE, 60 Hz/7 kHz, 4:1, 1W): < 0.07%
USB
Bit Depth: 24-bit
Sample Rate: 48 kHz
Device Charging: Up to 5 W
Bluetooth Wireless Technology
Version: 4.2, Class 2
Mode: Bluetooth Classic
Supported Profiles:
Hands-Free Profile 1.7 (HFP)
Audio/Video Remote
Control Profile 1.6 (AVRCP)
Advanced Audio
Distribution Profile 1.3 (A2DP)
Supported Codecs:
CVSD (8 kHz)
mSBC (16 kHz)
SBC (44.1 kHz)
SBC (48 kHz)
Maximum Transmit Power:
BER/EDR: 6.43 dBm (EIRP)
BLE: 7.69 dBm (EIRP)
Receive Sensitivity (0.1% BER): -88 dBm
Frequency Band: 2402-2480 MHz

Wireless Range: Up to 100 feet (30 m)
Environmental
Ambient Operating
Temperature Range: 32-104° F (0-40° C)
Humidity: 0-95% relative humidity (non-condensing)
Altitude: 0-6,600 ft (0-2000 m) MSL
Overall Dimensions
Height: 1.8 inches (46 mm)
Width: 11.2 inches (284 mm)
Depth: 6.9 inches (175 mm)
Weight: 2.0 lbs (0.9 kg)
Compliance
FCC Part 15B (USA)
UL and C-UL listed (USA and Canada)
CE Marked (Europe)
RoHS Directive (Europe)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.