Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Biamp Tesira AMP-450BP - 100V pojačalo



Šifra: 15432
Kategorija prozivoda: 100V Pojačala
Proizvođač: Biamp

Cena: 104.400,00 rsd

Product Features
Four channels; 3 watts of continuous power per channel
Burst mode to handle peak signals in accordance with ANSI/CTA-2006-B; supports up to 50 watts (4Ω load) or 30 watts (8Ω load) per channel
Powered by PoE+ (IEEE 802.3at Class 4, 30W)
RJ-45 connectors enable termination-free connections to compatible speakers like the Desono C-IC6
Class D amplifier topology
Fanless operation
BPAK accessory included
Audible locate function available on the front panel
Includes internal limiter function
Software-selectable power versus channel count
Evaluated to the requirements of UL 2043 and is suitable for use in air handling spaces
Configurable via Tesira software
CE marked, UL listed, and RoHS compliant
Covered by Biamp Systems’ five-year warranty

Product Specifications
General
Network Connection: RJ-45 with Ethernet cable (Cat 5e and above)
Number of Channels: 4
Connectors: RJ-45
Amplifier Topology: Class D
Burst Power Output (per ANSI/CTA-2006-B @ 1kHz):
4Ω (per channel): 50W
8Ω (per channel): 30W
Continuous Power Output:
Single Channel Driven (4Ω, 8Ω): 15W
Dual Channel Driven, (4Ω, 8Ω): 7W
Four Channel Driven, (4Ω, 8Ω): 3W
THD+N (20Hz-20kHz, at continuous power): < 0.3%
Frequency Response (20Hz-20kHz): ± 1dB
Dynamic Range (20Hz-20kHz BW): > 90dB
Minimum Operational Load: 4Ω
Intermodulation distortion (SMPTE): <0.3%
Cross Talk (channel to channel @ 1kHz): < -90dB
Cooling: Convection

Power: PoE+ (IEEE 802.3at Class 4 , 30W)
Indicators:
Power Indicator (Green/Yellow/Red LED)
Amp Status Indicator (Green/Yellow/Red LED)
Physical
Dmensions:
Height: 1.2 inches (30mm)
Width: 7.7 inches (195mm)
Depth: 4.7 inches (120mm)
Weight: 1.5 lbs (0.7 kg)
Environmental:
Ambient Operating Temperature Range: 32 - 104° F (0 - 40° C)
Humidity: 0-95% relative humidity (non-condensing)
Altitude: 0-10,000 ft (0-3000m) MSL
Compliance:
FCC Part 15B (USA)
UL and C-UL listed (USA and Canada)
CE Marked (Europe)
KCC (Korea)
RoHS Directive (Europe)
Evaluated to the requirements of UL 2043 and is suitable for use in air handling spaces

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.