

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

## Polk Audio R600 Black Podnostojeći Zvučnik

Šifra: 15454  
Kategorija proizvoda: Podnostojeći Zvučnici  
Proizvođač: Polk audio

**Cena: 59.880,00 rsd**

Polk Audio R600 Black Podnostojeći Zvučnik WHAT

BETTER SOUNDS LIKE

The Reserve Series incorporates groundbreaking Polk technologies found on our award-winning Legend Series to bring its flagship sound to more people.

SIT RIGHT EVERYWHERE

PINNACLE RING RADIATOR TWEETER

The Pinnacle Ring Radiator Tweeter's distinctive pointed shape guides the dispersion of high frequency sounds around a room. This innovation widens the sweet spot and allows you freedom to enjoy your music and movies wherever you choose to sit.

STRENGTH IN MOTION

TURBINE CONE WOOFER

Our pioneering turbine design delivers a significant increase in cone rigidity without increasing mass. This innovation means the woofer can move with increased accuracy and speed to deliver enhanced sound resolution, enabling you to experience a breathtaking level of detail in your music and movies.

CLEAN, DETAILED, EFFORTLESS BASS

POWER PORT 2.0

Polk's new Power Port 2.0 is the latest version of our successful Power Port technology. In addition to Power Port's carefully engineered port design that smooths the flow of air as it exits the cabinet through the port, X-Port adds a set of closed-pipe absorbers that are specifically tuned to unwanted cabinet and port resonances. Together, these two technologies combine to function as Power Port 2.0 to deliver smooth,

detailed audio. Combined with dual 8" woofers, you'll get louder, cleaner bass while minimizing turbulence and port noise.

## FORM AND FUNCTION

### EXCEPTIONAL CABINETRY

Reserve's sleek cabinetry hides a world of audio innovation. Cabinets are carefully cross-braced to best eliminate unwanted interior resonances. Rounded exterior corners help disperse sound broadly around the room with minimal diffraction, creating an open sound stage.

### MULTIDIMENSIONAL SOUND

### OPTIONAL HEIGHT MODULE

For immersive vertical sound, add compatible Reserve R900 height modules (sold separately). These optional height modules perform beautifully with the latest home theater technologies, including: Dolby Atmos, DTS, DTS:X, DTS:X Virtual, IMAX Enhanced, and Auro-3D.

### CERTIFIABLY EXCELLENT

### HI-RES CERTIFIED, DOLBY ATMOS ENABLED & IMAX ENHANCED

The Reserve Series sets the benchmark for music and movie audio excellence

# SPECIFICATIONS

## Specification

|              |                           |
|--------------|---------------------------|
| Speaker Type | Floorstanding Loudspeaker |
|--------------|---------------------------|

|               |      |
|---------------|------|
| UOM (Sold As) | Each |
|---------------|------|

TRANSDUCER

|         |                           |
|---------|---------------------------|
| Tweeter | 1" Pinnacle Ring Radiator |
|---------|---------------------------|

|                    |   |
|--------------------|---|
| Mid-range/Mid-bass | - |
|--------------------|---|

|         |                       |
|---------|-----------------------|
| Woofers | Two 6 ½” Turbine Cone |
|---------|-----------------------|

|                            |              |
|----------------------------|--------------|
| Overall Frequency Response | 35Hz - 50kHz |
|----------------------------|--------------|

|                                  |              |
|----------------------------------|--------------|
| Frequency Response (-3dB limits) | 43Hz - 38kHz |
|----------------------------------|--------------|

|                             |           |
|-----------------------------|-----------|
| Recommended Amplifier Power | 25 - 200W |
|-----------------------------|-----------|

|                                |              |
|--------------------------------|--------------|
| Amplifier Output Compatibility | 8Ω / 6Ω / 4Ω |
| Minimum Impedance (ohms)       | 4.0Ω         |
| Sensitivity (2.83V/1m)         | 87.5dB       |

CROSSOVER

|  |      |
|--|------|
| Tweeter/Mid-range Crossover Frequency  | 2700 |
| Mid-range/Mid-bass Crossover Frequency | -    |

MEASUREMENTS

|   |   |
|---|---|
| Product Dims W x H x D (Includes width of feet) | 280.7 x 1063.8 x 381.6mm<br>11 x 41.9 x 15 in |
| Product Weights (each)                          | 47.3 lbs/21.5                                 |
| Shipping Weight                                 | 58.2 lbs/26.4 kg                              |

CABINETRY

|                                    |                                     |
|------------------------------------|-------------------------------------|
| New CRC (Mid-Range Enclosure Type) | -                                   |
| Mid-Bass / Woofer Enclosure Type   | Floor Firing Power Port with X-Port |
| Available Finishes                 | Black / Walnut / White              |
| Feet                               | Spike and Pad                       |
| Wall-Mountable (keyhole slots)     | No                                  |
| Binding Posts: Nickel-plated 5-Way | Single                              |

Certifications (Non-Safety and Regulatory)

|                       |  |
|-----------------------|--|
| Hi-Res Certified      | Yes  |
| IMAX Certified        | Yes  |
| Shipping Dims (WxHxD) | 494 x 374 x 1152mm<br>(19.4 x 14.7 x 45.35) in |