

MACKIE EM-89D

Šifra: 15484
Kategorija proizvoda: Vokalni Mikrofoni
Proizvođač: MACKIE

Cena: 7.080,00 rsd



The EM-89D utilizes a cardioid polar pattern, which rejects sound behind the mic to reduce the pickup of stage bleed and allow higher gain before feedback. The mic's dynamic moving-coil design requires no batteries or phantom power, and the balanced 3-pin XLR output ensures proper connectivity with stage boxes, mixers, and portable PA systems. The EM-89D includes a mic clip, an XLR cable, and a zipper pouch.

Mackie EM-89D Specs

Microphone

Form Factor	Handheld / Stand/Boom Mount
Sound Field	Mono
Operating Principle	Pressure Gradient
Capsule	1 x Dynamic
Polar Pattern	Cardioid
Orientation	End Address
Circuitry	Solid-State
Pad	<i>None</i>
High-Pass Filter	<i>None</i>
Tone Adjustment	<i>None</i>

Indicators	<i>None</i>
On-Board Controls	<i>None</i>
Windscreen	Built-In

Performance

Frequency Range	50 Hz to 16 kHz
Impedance	600 Ohms \pm 30% at 1 kHz
Sensitivity	-52 dBV/Pa at 1 kHz

Connectivity

Output Connectors (Analog)	1 x XLR 3-Pin Male (on Mic)
Headphone Connector	<i>None</i>
Number of Conductors	2

Power

Operating Voltage	Not Specified by Manufacturer
-------------------	-------------------------------

Physical

Color	Black
Mounting	Mic Clip (Included)
Dimensions	ø: 2 x L: 7.3" / ø: 5.08 x L: 18.54 cm
Weight	0.66 lb / 0.3 kg